

Title (en)

Device for winding a web of material onto core tubes.

Title (de)

Vorrichtung zum Aufwickeln von Materialbahnen auf Wickelwellen.

Title (fr)

Machine pour enrouler des bandes de matière en bobines.

Publication

**EP 0538566 B1 19950719 (DE)**

Application

**EP 92113336 A 19920805**

Priority

- DE 4135163 A 19911024
- DE 4200478 A 19920110

Abstract (en)

[origin: CA2081241A1] A DEVICE FOR WINDING WEBS OF MATERIAL, ONTO WINDING SHAFTS A device for winding webs of material onto winding shafts comprises a movable bearing supporting a winding shaft during winding, through which the supply roll being formed can be moved towards a contact roller and which can be moved in a position away therefrom for the removal of the completely wound supply roll. A new winding shaft accelerated approximately up to the speed of the web and onto which the leading end of the web formed by a severance cut can be wound, is inserted in the movable bearings by a means. In order to prevent the supply roll with its increasing weight from being supported completely on the contact roller, which may cause damage to the web, the movable bearing is provided. The bearing comprises pairs of holding means each pair of which can be moved synchronously with the other pair and also independently thereof. The pairs are adapted to hold a supply roll jointly as well as to hold individually a completely wound supply roll or a winding shaft with the leading end of the web wound thereon.

[origin: CA2081241A1] A device for winding webs of material onto winding shafts comprises a movable bearing supporting a winding shaft during winding, through which the supply roll being formed can be moved towards a contact roller and which can be moved in a position away therefrom for the removal of the completely wound supply roll. A new winding shaft accelerated approximately up to the speed of the web and onto which the leading end of the web formed by a severance cut can be wound, is inserted in the movable bearings by a means. In order to prevent the supply roll with its increasing weight from being supported completely on the contact roller, which may cause damage to the web, the movable bearing is provided. The bearing comprises pairs of holding means each pair of which can be moved synchronously with the other pair and also independently thereof. The pairs are adapted to hold a supply roll jointly as well as to hold individually a completely wound supply roll or a winding shaft with the leading end of the web wound thereon.

IPC 1-7

**B65H 19/22**

IPC 8 full level

**B65H 19/22** (2006.01)

CPC (source: EP US)

**B65H 19/2253** (2013.01 - EP US); **B65H 2301/41358** (2013.01 - EP US); **B65H 2301/41468** (2013.01 - EP US); **B65H 2408/236** (2013.01 - EP US)

Cited by

EP0905069A1; EP0584716A3; EP0595229A3; US6834824B1; US7168651B2; WO9630293A1

Designated contracting state (EPC)

AT CH DE DK ES FR GB IT LI

DOCDB simple family (publication)

**EP 0538566 A1 19930428**; **EP 0538566 B1 19950719**; AT E125235 T1 19950815; CA 2081241 A1 19930425; CA 2081241 C 20020319; CZ 281402 B6 19960911; CZ 321492 A3 19930915; DE 4200478 A1 19930429; DE 59202942 D1 19950824; DK 0538566 T3 19951218; ES 2074318 T3 19950901; JP 3293899 B2 20020617; JP H05193794 A 19930803; TW 211596 B 19930821; US 5251837 A 19931012

DOCDB simple family (application)

**EP 92113336 A 19920805**; AT 92113336 T 19920805; CA 2081241 A 19921023; CS 321492 A 19921023; DE 4200478 A 19920110; DE 59202942 T 19920805; DK 92113336 T 19920805; ES 92113336 T 19920805; JP 28625392 A 19921023; TW 81106231 A 19920806; US 94288992 A 19920910