

Title (en)
Toroidal inductance

Title (de)
Toroiddrossel

Title (fr)
Inductance toroidale

Publication
EP 0540958 B1 19960417 (DE)

Application
EP 92118169 A 19921023

Priority
DE 4136176 A 19911102

Abstract (en)
[origin: EP0540958A1] In order to be able to limit, for example, short-circuit currents of 100 kA or more in high-power converters, a toroidal inductor (1) having a plurality of turns is used, which has a plurality of segmented partial windings (2). Each partial winding (2) is in electrically conductive contact with at least one connecting element (3) in order to be able to connect adjacent partial windings (2) in series or a plurality of partial windings (2) in parallel. The partial windings (2) have an approximately identical current cross-section over their length; their width (a) is less in the inner region (4) than their width (b) at the peripheral outer edge (5). In consequence, a large number of turns and a modular inductor construction are possible, with a high mechanical strength. <IMAGE>

IPC 1-7
H01F 37/00; **H01F 27/28**

IPC 8 full level
H01F 27/28 (2006.01); **H01F 37/00** (2006.01)

CPC (source: EP)
H01F 27/2895 (2013.01); **H01F 37/005** (2013.01)

Cited by
EP1772877A1; EP0669629A1; EP2495742A1; US6787599B1

Designated contracting state (EPC)
DE FR GB IT

DOCDB simple family (publication)
EP 0540958 A1 19930512; **EP 0540958 B1 19960417**; DE 4136176 A1 19930506; DE 59206030 D1 19960523; JP H05283252 A 19931029

DOCDB simple family (application)
EP 92118169 A 19921023; DE 4136176 A 19911102; DE 59206030 T 19921023; JP 29414992 A 19921102