

Title (en)
KNAPSACK.

Title (de)
RUCKSACK.

Title (fr)
SAC A DOS.

Publication
EP 0542739 B1 19950301 (DE)

Application
EP 90912006 A 19900810

Priority
EP 9001325 W 19900810

Abstract (en)
[origin: WO9202158A1] A knapsack has at least one stiffening element (2) received in pockets (6) provided on the back wall (3) and concavely curved (seen from outside) at least in parts, in the longitudinal and/or transversal direction. The stiffening element (2) concavely deforms the back wall (3) in the longitudinal and/or transversal directions. An elastic support band (4) extends between a lower area of the stiffening element (2) and a supporting net (5) stretched in the upper area of the stiffening element (2), bridging the concavity. This support band (4) can for example extend between a lower marginal area of the stiffening element (2) and the supporting net (5). In order to make it easier to mount and dismount the knapsack, and to ensure a reliable seat of the same, the stiffening element (2) is a flat one-piece element, provided if necessary with openings, which when it is curved is releasably stretched in the longitudinal and transversal directions only by its upper and lower ends between upper and lower pockets (6) in the back wall (3).

IPC 1-7
A45F 3/04

IPC 8 full level
A45F 3/04 (2006.01)

CPC (source: EP KR US)
A45F 3/04 (2013.01 - EP KR US); **A45F 2003/125** (2013.01 - EP KR US)

Cited by
WO2015041379A1

Designated contracting state (EPC)
AT BE CH DE DK ES FR GB IT LI NL SE

DOCDB simple family (publication)
WO 9202158 A1 19920220; DE 59008611 D1 19950406; DE 9090116 U1 19910529; EP 0542739 A1 19930526; EP 0542739 B1 19950301; KR 0156271 B1 19981201; KR 930701121 A 19930611; US 5366126 A 19941122

DOCDB simple family (application)
EP 9001325 W 19900810; DE 59008611 T 19900810; DE 9090116 U 19900810; EP 90912006 A 19900810; KR 930700380 A 19930210; US 96914193 A 19930310