Title (en)

Clip binder for unperforated sheets of paper

Title (de)

Klemmhefter für ungelochtes Schriftgut

Title (fr)

Classeur à fixation par serrage pour feuilles de papier non-perforées

Publication

EP 0544061 B1 19960320 (DE)

Application EP 92

EP 92114433 A 19920825

Priority

DE 4138643 A 19911125

Abstract (en)

[origin: EP0544061A1] The invention relates to a clip binder for unperforated sheets of paper (30), having a front cover and a back cover (14, 18) in each case articulated on a binder spine (10), and having a clamp (22) which is substantially U-shaped in cross-section and is capable of limited displacement transversely to the binder spine (10) between a release position and a clamping position. The front leg (26) of the clamp can be pushed, by means of a clamping rib (28) projecting towards the rear clamping leg (24) and with intermediate clamping of the sheets of paper (30), onto a push-on tongue (34) arranged in the region of a cut-away (32) situated in the front cover (14) and partly engaging over the sheets of paper (30). In order to permit particularly simple manufacture of the clip binder, for example from a one-piece blank of cardboard material, the push-on tongue (34) is moulded on by its root (36) on the front cover (14) at a distance from the spine edge (12) thereof and, from there, engages over the cut-away (32) present in the front cover (14), towards the binder spine (10). Furthermore, the limiting stop (38) is arranged on the side of the free end of the push-on tongue (34) facing away from the back cover (18). <IMAGE>

IPC 1-7

B42F 9/00

IPC 8 full level

B42F 9/00 (2006.01)

CPC (source: EP) B42F 9/007 (2013.01)

Cited by

CN104742023A; NL1022470C2; US5459596A; US5600461A; WO2004065226A3; WO0029226A1

Designated contracting state (EPC) DE FR GB IT

DOCDB simple family (publication)

EP 0544061 A1 19930602; EP 0544061 B1 19960320; DE 4138643 A1 19930527; DE 59205756 D1 19960425

DOCDB simple family (application)

EP 92114433 A 19920825; DE 4138643 A 19911125; DE 59205756 T 19920825