

Title (en)

Apparatus and method for feeding a weft yarn.

Title (de)

Vorrichtung und Verfahren zum Zuführen von Schussfaden.

Title (fr)

Dispositif et méthode pour alimenter de fil de trame.

Publication

**EP 0544623 A1 19930602 (EN)**

Application

**EP 92810912 A 19921124**

Priority

JP 34029391 A 19911128

Abstract (en)

To draw a cut weft end Y2 into a weft guide nozzle 16 and then to introduce the same weft end Y2 into a weft inserting main nozzle 13 with certainty, thereby stabilizing the operation of feeding the weft properly through the guide nozzle 16 and the main nozzle 13. [STRUCTURE] The weft end Y2 formed by cutting a weft with a weft cutter 22 at a predetermined position is drawn into the weft guide nozzle 16 under the influence of suction force created by high-pressure air flow supplied from the valve V1 and thereafter the weft end Y2 is introduced into the main nozzle 13 by a low-pressure air flow supplied from the valve V4 whose pressure is set at an optimum level for insertion of the weft end into the main nozzle 13. <IMAGE>

IPC 1-7

**D03D 47/34**

IPC 8 full level

**D03D 51/00** (2006.01); **D03D 47/34** (2006.01)

CPC (source: EP)

**D03D 47/34** (2013.01)

Citation (search report)

- [X] EP 0418948 A1 19910327 - PICANOL NV [BE]
- [X] EP 0355281 A1 19900228 - NISSAN MOTOR [JP]
- [AP] EP 0488954 A1 19920603 - TOYODA AUTOMATIC LOOM WORKS [JP]

Cited by

EP0796936A3

Designated contracting state (EPC)

BE DE FR IT

DOCDB simple family (publication)

**EP 0544623 A1 19930602**; JP H05148742 A 19930615

DOCDB simple family (application)

**EP 92810912 A 19921124**; JP 34029391 A 19911128