

Title (en)

Method and device for dyeing a textile sheet-like material.

Title (de)

Verfahren zum Färben einer textilen Stoffbahn und Vorrichtung zum Durchführen des Verfahrens.

Title (fr)

Procédé et appareil de teinture d'une matière textile en bande.

Publication

**EP 0546275 A1 19930616 (DE)**

Application

**EP 92117364 A 19921010**

Priority

DE 4140600 A 19911210

Abstract (en)

[origin: JPH05272051A] PURPOSE: To enable color characteristics to be amended by measuring the color characteristics of a belt material at the positions before and after a dye-fixing device connected to the rear part of a foulard vessel by a same color characteristic-detecting assembly when carrying out the dyeing by using the dyeing foulard vessel. CONSTITUTION: A textile belt material 1 is guided through a guide roller 2 and a dipping roller 3 into a dye liquid bath 5 in a foulard vessel 4 so as to penetrate a dye liquid bath 5, and dehydrated by the mutual pressing pressure of both rollers 8 of a squeezer 6 to a moist valve expressed by an initial moisture. The belt material 1 is traveled in a drying and dye-fixing device 13 via a color characteristic-detecting assembly 10 and a moisture-measuring device 11, and guided through a deflection roller 14 to a roller pair. The dried and fixed belt material fraction 16 is positioned in parallel to a belt material fraction 17 between rollers 15 and between the squeezer 6 and the dye-fixing device 13, and at the same distance from the detecting head part 21 of the color characteristic-detecting assembly 10. The detected and measured results by the color characteristic-detecting assembly 10 and the moisture-measuring device 11 are fed to a computer 23 and the squeezer 6 is thereby controlled.

Abstract (de)

Um beim Färben mit einem Färbefoulard Fehlfärbungen infolge unterschiedlichen Stoffbahnverhaltens und/oder unterschiedlicher Farbtypen frühzeitig zu erkennen und korrigierend in die Arbeit des Foulards einzugreifen, wird die Farbe der Stoffbahn (1) vor und nach einer dem Foulard nachgeschalteten Trocken- bzw. Farbfixiereinrichtung (13) mit Hilfe ein und desselben Farbmeßgeräts (10) jeweils unmittelbar gemessen. Das Meßergebnis wird zur Steuerung des Quetschwerks (6) des Foulards und zur Korrektur der zugehörigen Programmierung herangezogen. <IMAGE>

IPC 1-7

**D06B 23/26**

IPC 8 full level

**D06B 3/18** (2006.01); **D06B 23/26** (2006.01)

CPC (source: EP US)

**D06B 23/26** (2013.01 - EP US)

Citation (search report)

- [Y] CA 1169140 A 19840612 - SENTROL SYSTEMS LTD
- [YD] DE 3925444 A1 19910207 - MONFORTS GMBH & CO A [DE]
- [A] EP 0093446 A1 19831109 - HOECHST AG [DE]
- [A] US 3811834 A 19740521 - SCHWEMMER M, et al

Designated contracting state (EPC)

BE CH DE ES FR GB LI NL

DOCDB simple family (publication)

**DE 4140600 C1 19930211**; EP 0546275 A1 19930616; JP H05272051 A 19931019; US 5284035 A 19940208

DOCDB simple family (application)

**DE 4140600 A 19911210**; EP 92117364 A 19921010; JP 33032092 A 19921210; US 98845192 A 19921210