

Title (en)

Rotatable selector switch with cam shaft or cam wheel positionable by an indexing means

Title (de)

Drehwahlschalter mit einer durch eine Rastung festlegbaren Schaltnockenwelle oder Schaltnockenscheibe

Title (fr)

Interrupteur de sélection rotatable avec un arbre à cames ou un disque à cames arrêtable par un moyen d'indexation

Publication

EP 0549870 B1 19960327 (DE)

Application

EP 92118849 A 19921104

Priority

DE 4141110 A 19911213

Abstract (en)

[origin: EP0549870A1] In the case of a rotary selector switch, whose cam shaft or cam disc control numerous switching contacts, the cam shaft or cam disc is locked in the angular position corresponding to the respective switching position by means of a latching plunger (18) which is pressed against a latching star (16) by means of a spring which acts axially. A U-shaped leaf spring (28), whose two limbs enclose the latching plunger, is inserted into the latching chamber (12). In the upper part, the latching chamber is provided with an expansion (30) in which the latching plunger can move to both sides together with the upper parts of the leaf spring. The leaf spring is deflected by the latching tooth of the latching star during switching, and its prestress caused thereby ensures a fast transition over the unstable intermediate position. <IMAGE>

IPC 1-7

H01H 19/62; H01H 3/50

IPC 8 full level

H01H 3/50 (2006.01); **H01H 19/11** (2006.01); **H01H 19/62** (2006.01)

CPC (source: EP)

G05G 5/06 (2013.01); **H01H 19/11** (2013.01)

Cited by

CN102549696A; EP0932019A3; ITRM20100526A1; GB2336722A; GB2336722B; EP0780866A1; FR2742914A1; CN103594275A; US6613997B2; WO0218882A1; WO2012046263A1; WO2014134683A1; WO2005122203A1

Designated contracting state (EPC)

DE FR GB IT SE

DOCDB simple family (publication)

EP 0549870 A1 19930707; EP 0549870 B1 19960327; DE 4141110 A1 19930617; DE 59205854 D1 19960502

DOCDB simple family (application)

EP 92118849 A 19921104; DE 4141110 A 19911213; DE 59205854 T 19921104