

Title (en)

Device for gear train separation.

Title (de)

Einrichtung zur Getriebezugtrennung.

Title (fr)

Dispositif pour la séparation d'un train d'engrenage.

Publication

EP 0549884 B1 19950906 (DE)

Application

EP 92120033 A 19921125

Priority

DE 4141817 A 19911218

Abstract (en)

[origin: EP0549884A1] In sheet-fed rotary printing machines for perfecting, a double gearwheel with a coupling device is provided in the gear train. Said coupling device is to be made to function automatically whilst the double gearwheel is to remain simple in terms of construction and not additionally loaded in terms of weight. <??>The coupling device consists of a substantially two-part annular mechanism (36, 37) which is attached movably to the machine frame (26). Together with an outer ring (37) an inner ring (36) forms a compression space which is pressurised with hydraulic fluid for uncoupling. In this process, the rings (36, 37) are pressed apart until the outer ring (37) strikes against a clamping device for the gearwheel ring on the double gearwheel and the inner ring (36) against an unlocking element (39) on the main gearwheel and the clamping force of the clamping device on the gearwheel ring is reduced. The forces to be applied are conducted inside the double gearwheel. For renewed clamping, the annular space is again made pressureless. In the state of rest, the coupling device does not touch the gearwheel. <IMAGE>

IPC 1-7

B41F 13/00

IPC 8 full level

B41F 21/10 (2006.01); **B41F 13/00** (2006.01); **F16D 25/063** (2006.01)

CPC (source: EP US)

B41F 13/0008 (2013.01 - EP US)

Cited by

EP0635364A1; EP0655329B2; EP0578960B2

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB GR IT LI LU NL PT SE

DOCDB simple family (publication)

EP 0549884 A1 19930707; EP 0549884 B1 19950906; AT E127395 T1 19950915; DE 4141817 A1 19930701; DE 4141817 C2 19931007; DE 59203583 D1 19951012; JP 2758329 B2 19980528; JP H05254093 A 19931005; US 5265528 A 19931130

DOCDB simple family (application)

EP 92120033 A 19921125; AT 92120033 T 19921125; DE 4141817 A 19911218; DE 59203583 T 19921125; JP 33405592 A 19921215; US 99257092 A 19921218