

Title (en)

Improved boss for a filament wound pressure vessel.

Title (de)

Polstück für ein fasergewickeltes Druckgefäß.

Title (fr)

Coulot et coupelle d'un réservoir sous pression à filament enroulé.

Publication

EP 0550951 B1 19951115 (EN)

Application

EP 92307243 A 19920807

Priority

- US 81861992 A 19920110
- US 90272592 A 19920623

Abstract (en)

[origin: EP0550951A1] A boss (16) is disposed in a polar opening (18) in a pressure vessel (10) which has a filament wound outer shell (12) and a non-metallic internal liner (14). The boss has a tubular neck (24) which projects outwardly from the vessel interior and an annular support flange (28) which extends radially from the internal end of the neck and supports the perimeter of the polar opening. An offset attachment flange (32) extends radially from the support flange and has two axially opposed surfaces (34,36) with locking grooves (40,42) formed therein. Each locking groove has a bottom wall intermediate a pair of mutually skewed sidewalls (50) for maintaining positive engagement with and retention of complementary respective tabs on the liner. In an application where the liner is a blow molded component, an injection molded interface member (82) is attached to the support flange and provides a site at which the liner is welded. <IMAGE>

IPC 1-7

F17C 13/00; F17C 1/16

IPC 8 full level

F16J 12/00 (2006.01); **F17C 1/16** (2006.01)

CPC (source: EP)

F17C 1/16 (2013.01); **F17C 2201/0109** (2013.01); **F17C 2203/0604** (2013.01); **F17C 2203/0619** (2013.01); **F17C 2203/0663** (2013.01); **F17C 2203/0673** (2013.01); **F17C 2205/0305** (2013.01); **F17C 2209/2118** (2013.01); **F17C 2209/2127** (2013.01); **F17C 2260/036** (2013.01); **F17C 2260/044** (2013.01); **F17C 2260/053** (2013.01)

Cited by

CN103363289A; DE10360953B4; DE112004002795B4; EP0664418A1; CN110220104A; US6230922B1; JP2015102180A; DE102006006902A1; DE102006006902B4; EP1950488A3; FR3025565A1; DE19631546C1; EP0821194A3; DE19526154A1; EP0753700A1; CN107420739A; EP0874187A1; CN105135207A; FR3035173A1; US7549555B2; US9103500B2; WO2013083174A1; WO9913263A1; WO2016034823A1; WO2016166326A1; DE102020134624A1; WO2022135872A1; WO9927293A3; WO2017165364A1; WO2007085277A1; WO2007085276A1; JP2014020440A; EP1258669B1; US7637285B2; US7959027B2; US8231028B2; EP2778499A1; DE102022211155A1

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB GR IT LI NL PT SE

DOCDB simple family (publication)

EP 0550951 A1 19930714; EP 0550951 B1 19951115; AT E130421 T1 19951215; AU 2631992 A 19930715; AU 653639 B2 19941006; BR 9204294 A 19930713; CA 2080856 A1 19930711; CA 2080856 C 20010130; CN 1032273 C 19960710; CN 1074281 A 19930714; DE 69206114 D1 19951221; DE 69206114 T2 19960418; EG 20012 A 19970227; HU 214759 B 19980528; HU 9300040 D0 19930428; HU T72870 A 19960528; JP 3517789 B2 20040412; JP H06137433 A 19940517; MX 9300077 A 19931201; MY 110573 A 19980829; NZ 245515 A 19941222; RU 2091648 C1 19970927

DOCDB simple family (application)

EP 92307243 A 19920807; AT 92307243 T 19920807; AU 2631992 A 19921008; BR 9204294 A 19921105; CA 2080856 A 19921019; CN 92112085 A 19921006; DE 69206114 T 19920807; EG 993 A 19930106; HU 9300040 A 19930108; JP 33679592 A 19921125; MX 9300077 A 19930108; MY PI19921720 A 19920925; NZ 24551592 A 19921218; RU 93005014 A 19930106