

Title (en)

Mould for a false floor formwork.

Title (de)

Schalungsmatrize für einen Hohlraumboden.

Title (fr)

Moule de coffrage pour un faux plancher surélevé.

Publication

EP 0551051 B1 19950524 (DE)

Application

EP 92810816 A 19921021

Priority

CH 4792 A 19920109

Abstract (en)

[origin: EP0551051A1] The shuttering mould has a comparatively rigid slab and a plurality of load-bearing feet (5) attached on one side of the slab (6). The load-bearing slab (6) consists preferably of pressed cellulose and the load-bearing feet (5) are produced preferably from polypropylene. On the underside of the load-bearing feet (5) there is arranged in each case a flexible neck collar (9) having an opening (8) through which, in the case of a load-bearing foot (5') not bearing at the bottom on an underfloor (1), floor material (4) applied at the top of the mould (3) can escape at the bottom. The neck collar (9) forms a seal with respect the underfloor (1) and prevents the escaped floor material (4) from escaping laterally. As a result, it is ensured that all the load-bearing feet (5, 5') rest on the bottom, even in the case of an uneven underfloor (1). However, it is possible to walk on the shuttering mould during mounting. <IMAGE>

IPC 1-7

E04F 15/024; **E01C 23/10**

IPC 8 full level

E01C 23/10 (2006.01); **E04F 15/024** (2006.01)

CPC (source: EP)

E01C 23/10 (2013.01); **E04F 15/02429** (2013.01)

Cited by

EP1031659A3; EP0803618A3; EP2476818A3

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB GR IT LI LU NL PT SE

DOCDB simple family (publication)

EP 0551051 A1 19930714; **EP 0551051 B1 19950524**; AT E123103 T1 19950615; DE 59202343 D1 19950629

DOCDB simple family (application)

EP 92810816 A 19921021; AT 92810816 T 19921021; DE 59202343 T 19921021