

Title (en)

METHOD FOR FORMING FIXED IMAGES

Publication

EP 0552785 A3 19931006 (EN)

Application

EP 93100934 A 19930121

Priority

JP 3443292 A 19920123

Abstract (en)

[origin: EP0552785A2] A method of forming fixed images of the present invention includes charging a photoconductor; exposing the photoconductor to light; applying a thermally dissociating encapsulated toner or an encapsulated toner whose shell is made of amorphous polyester to an electrostatic latent image formed on the photoconductor, thereby developing the electrostatic latent image to form a visible image; transferring the formed visible image to a recording medium; and fixing the transferred visible image onto the recording medium at a temperature of not more than 130 DEG C. The fixing is carried out using a heat roller-type fixing apparatus including a heat roller having a conductive elastomer layer formed in a uniform thickness, a pressure roller and a current supplying means. The steps of the fixing include passing an electric current into the conductive elastomer layer; and thermally fixing the visible image by heat generated in the conductive elastomer layer. <IMAGE>

IPC 1-7

G03G 15/20

IPC 8 full level

G03G 9/08 (2006.01); **G03G 9/093** (2006.01); **G03G 13/20** (2006.01); **G03G 15/20** (2006.01)

CPC (source: EP)

G03G 9/09328 (2013.01); **G03G 13/20** (2013.01); **G03G 15/2053** (2013.01)

Citation (search report)

- [XD] EP 0453857 A1 19911030 - KAO CORP [JP]
- [Y] DE 2306440 B2 19760429
- [AP] EP 0516062 A2 19921202 - KAO CORP [JP]
- [A] DE 3836857 A1 19890511 - SHARP KK [JP]
- [A] GB 2197619 A 19880525 - HITACHI METALS LTD
- [A] PATENT ABSTRACTS OF JAPAN vol. 011, no. 208 (P-593)(2655) 7 July 1987 & JP-A-62 030 280 (TOKAI RUBBER IND.) 9 February 1987
- [A] PATENT ABSTRACTS OF JAPAN vol. 009, no. 050 (P-339)(1773) 5 March 1985 & JP-A-59 189 381 (FUJI XEROX) 26 October 1984
- [A] PATENT ABSTRACTS OF JAPAN vol. 013, no. 316 (P-900)(3664) 18 July 1989 & JP-A-01 086 185 (OKI ELECTRIC IND.) 30 March 1989
- [A] PATENT ABSTRACTS OF JAPAN vol. 014, no. 185 (P-1036)13 April 1990 & JP-A-02 032 368 (CANON) 2 February 1990

Cited by

EP0642059A1; US5571652A; EP0615167A1; US5536612A; CN100340931C; EP0656568A1; US5567567A; EP0587036A3; US5529876A; US5763130A; EP0672957A3; US5565293A; EP0595347A1; US5443936A

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

EP 0552785 A2 19930728; EP 0552785 A3 19931006; JP H05204269 A 19930813

DOCDB simple family (application)

EP 93100934 A 19930121; JP 3443292 A 19920123