

Title (en)  
Lock.

Title (de)  
Schloss.

Title (fr)  
Serrure.

Publication  
**EP 0553509 A1 19930804 (EN)**

Application  
**EP 92203493 A 19921114**

Priority  
IL 10010791 A 19911120

Abstract (en)  
A method for operating a locking device in vandalism-prone environments including the steps of providing a lock including a lock cylinder (22) defining a keyway (26) having an egress opening in the interior end thereof, the egress opening being configured and arranged to allow foreign bodies (46) inserted into the keyway (26) to pass through the egress opening upon insertion of the key (60) and removing a foreign body (46) from the lock. <IMAGE>

IPC 1-7  
**E05B 17/00**; **E05B 17/12**

IPC 8 full level  
**E05B 9/10** (2006.01); **E05B 17/00** (2006.01); **E05B 17/12** (2006.01); **E05B 67/24** (2006.01)

CPC (source: EP)  
**E05B 9/105** (2013.01); **E05B 17/002** (2013.01); **E05B 17/12** (2013.01); **E05B 67/24** (2013.01); **E05B 2009/046** (2013.01)

Citation (search report)

- [A] US 4539829 A 19850910 - GIVOL BENNY [IL]
- [A] DE 8803472 U1 19880616
- [AD] US 3499209 A 19700310 - LAVIANA LAWRENCE J
- [A] GB 990987 A 19650505 - VIRO INNOCENTI SPA
- [A] DE 3443516 A1 19860605 - GELHARD EGON
- [AD] US 4464915 A 19840814 - MOSHE DOLEV [IL], et al

Cited by  
CN112780113A; US6047575A; US6046558A; EP0761915A3; FR2815067A1

Designated contracting state (EPC)  
AT BE CH DE DK ES FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)  
**EP 0553509 A1 19930804**; AU 2847592 A 19930527; AU 661734 B2 19950803; BR 9204588 A 19930525; CN 1072984 A 19930609; EC SP920882 A 19940321; HU 9203636 D0 19930428; HU T63676 A 19930928; IL 100107 A0 19920818; IL 100107 A 19950330; NO 924462 D0 19921119; NO 924462 L 19930521; PL 171267 B1 19970328; PL 296675 A1 19930809

DOCDB simple family (application)  
**EP 92203493 A 19921114**; AU 2847592 A 19921119; BR 9204588 A 19921120; CN 92112661 A 19921119; EC SP920882 A 19921112; HU 9203636 A 19921120; IL 10010791 A 19911120; NO 924462 A 19921119; PL 29667592 A 19921120