

Title (en)

Implantable pacemaker providing hysteresis in dual-chamber modes.

Title (de)

Implantierbarer Herzschrittmacher welcher eine Hysterese bei Zweikammerbetriebsart erzeugt.

Title (fr)

Stimulateur cardiaque implantable produisant une hystérésis en fonctionnement double chambre.

Publication

EP 0559193 A2 19930908 (EN)

Application

EP 93103481 A 19930304

Priority

US 84630892 A 19920305

Abstract (en)

An implantable pacemaker provides three types of hysteresis for use in dual chamber and/or atrial tracking modes, such as VDI, VDD, DDI, DDD, VDIR, VDDR, DDIR or DDDR. The pacemaker defines a basic atrial escape interval (AEI) that defines the maximum time between a ventricular event and a subsequent atrial event, as well as an AV delay (AVD) that defines the maximum time between an atrial event and the next ventricular event. The sum of AEI plus AVD thus sets the rate at which stimulation pulses are generated in the absence of sensed natural cardiac activity. A first type of hysteresis, atrial escape rate hysteresis, causes the AEI to be extended upon sensing natural atrial beats (P-waves). The increased AEI remains in force so long as natural P-waves continue to be sensed during the AEI. Should a P-wave not be sensed during the AEI, a stimulation pulse is generated and the AEI reverts to its initial value. A second type of hysteresis, atrial-induced AV delay hysteresis, extends the next AVD and shortens the AEI in response to sensing a P-wave, thereby keeping the pacemaker's programmed rate the same. A third type of hysteresis, ventricular-induced AV delay hysteresis, extends the next AVD and shortens the AEI in response to sensing an R-wave. Any desired combination of the three types of hysteresis may be programmably selected for use within the pacemaker. <IMAGE>

IPC 1-7

A61N 1/368

IPC 8 full level

A61N 1/365 (2006.01); **A61N 1/362** (2006.01); **A61N 1/368** (2006.01)

CPC (source: EP US)

A61N 1/3622 (2013.01 - EP US); **A61N 1/368** (2013.01 - EP US); **A61N 1/3682** (2013.01 - EP US)

Cited by

AU681942B2; US5891175A; EP0589860A3; EP0661076A1; FR2714610A1; US5540726A; WO9524944A1; WO9829159A1; EP0624386B1

Designated contracting state (EPC)

DE FR GB IT NL SE

DOCDB simple family (publication)

US 5237992 A 19930824; AU 3378993 A 19930909; AU 654641 B2 19941110; DE 69333033 D1 20030717; DE 69333033 T2 20040429; EP 0559193 A2 19930908; EP 0559193 A3 19970326; EP 0559193 B1 20030611; JP H067458 A 19940118

DOCDB simple family (application)

US 84630892 A 19920305; AU 3378993 A 19930224; DE 69333033 T 19930304; EP 93103481 A 19930304; JP 6935493 A 19930303