

Title (en)
Security device for running webs.

Title (de)
Sicherheitsvorrichtung für laufende Bahnen.

Title (fr)
Dispositif de sécurité des bandes en marche.

Publication
EP 0563645 A1 19931006

Application
EP 93104019 A 19930312

Priority
DE 4210190 A 19920328

Abstract (en)
The invention relates to a safety device for running webs, in particular to avoid stopping and coiling in rotary printing machines, having a cutting knife (8, 19) which can be pivoted into the region of the web path. In order to design a device of this type in such a way that with simple technical means both free access to the cutting knife is prevented and unimpeded conducting-away of the cut-off web from the region of an assembly which is in each case at risk due to stopping and coiling is achieved, the cutting knife with its holder is an integral constituent of a two-part covering (6, 9) whose guard which projects in the direction of the web path covers the cutting edge of the subsequent guard functioning as the cutting knife on the operating side, and the latter guard exposes a run-out gap (17) towards the projecting guard in the cutting position for the cut-off running web and thereby serves as a conducting surface for the web. <IMAGE>

Abstract (de)
Die Erfindung betrifft eine Sicherheitsvorrichtung für laufende Bahnen, insbesondere zur Vermeidung von Stoppern und Wicklern in Rotationsdruckmaschinen, mit einen in den Bereich des Bahnlaufes schwenkbaren Schneidmesser (8,19). Um eine derartige Vorrichtung so zu gestalten, daß mit einfachen technischen Mitteln sowohl ein freier Zugriff auf das Schneidmesser verhindert als auch eine ungehinderte Ableitung der abgeschnittenen Bahn aus dem jeweils von Stoppern und Wicklern gefährdeten Bereich eines Aggregates erreicht wird, ist das Schneidmesser mit seiner Halterung integraler Bestandteil einer zweiteiligen Abdeckung (6,9), deren in Richtung des Bahnlaufes voranstehender Schutz die Schneidkante des als Schneidmesser fungierenden nachfolgenden Schutzes zur Bedienseite abdeckt und letzterer in der Schnittstellung zum voranstehenden Schutz einen Auslaufspalt (17) für die abgechnittene laufende Bahn frei gibt und dabei für die Bahn als Leitfläche dient. <IMAGE>

IPC 1-7
B41F 13/02

IPC 8 full level
B41F 13/02 (2006.01); **B41F 33/18** (2006.01)

CPC (source: EP)
B41F 33/18 (2013.01); **B41P 2233/22** (2013.01)

Citation (search report)
• [AD] DE 1132563 B 19620705 - ALBERT SCHNELLPRESSEN
• [A] EP 0037642 A1 19811014 - BALDWIN TECHNOLOGY CORP [US]
• [A] EP 0318853 A2 19890607 - KOTTERER GRAFOTEC [DE]

Cited by
CN103612469A; FR2833205A1; EP0732207A1; US5615610A

Designated contracting state (EPC)
DE FR GB SE

DOCDB simple family (publication)
EP 0563645 A1 19931006; **EP 0563645 B1 19960306**; DE 4210190 A1 19930930; DE 59301756 D1 19960411

DOCDB simple family (application)
EP 93104019 A 19930312; DE 4210190 A 19920328; DE 59301756 T 19930312