

Title (en)

Electrically or mechanically operated locking device with narrow profile.

Title (de)

Elektrisch oder mechanisch betätigbare Schlossvorrichtung mit schmalem Profil.

Title (fr)

Dispositif de serrure à profil étroit, à manoeuvrement électrique ou mécanique.

Publication

**EP 0565803 B1 19950705 (FR)**

Application

**EP 92440044 A 19920414**

Priority

EP 92440044 A 19920414

Abstract (en)

[origin: EP0565803A1] Electrically or mechanically operated narrow-profile lock device. Formed in the shank (20) of the bolt (2) is a notch (21) which is perpendicular to the displacement of the said bolt (2) and which circumscribes the eccentric loose roller (30) of a ring (3) mounted on an axle (11) and driven in rotation as a result of the linear displacement of a slide (4) under the effect of a gearwheel (32) fixed to the said ring (3) and meshing with a rack (41) fixed to the said slide (4), the displacement of which is actuated electrically or mechanically. <IMAGE>

IPC 1-7

**E05B 47/00**

IPC 8 full level

**E05B 47/00** (2006.01); **E05B 47/02** (2006.01); **E05B 63/00** (2006.01)

CPC (source: EP)

**E05B 47/0012** (2013.01); **E05B 47/026** (2013.01); **E05B 63/0017** (2013.01); **E05B 2047/002** (2013.01); **E05B 2047/0024** (2013.01); **E05B 2047/0086** (2013.01)

Cited by

EP1048805A1; FR2792964A1; GB2321277A; GB2321277B; CN102619392A; EP3578741A1; IT201800006138A1; WO9719240A1

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB GR IT LI LU MC NL PT SE

DOCDB simple family (publication)

**EP 0565803 A1 19931020**; **EP 0565803 B1 19950705**; AT E124753 T1 19950715; DE 69203339 D1 19950810

DOCDB simple family (application)

**EP 92440044 A 19920414**; AT 92440044 T 19920414; DE 69203339 T 19920414