

Publication

**EP 0567092 A3 19940406**

Application

**EP 93106458 A 19930421**

Priority

DE 4213467 A 19920424

Abstract (en)

[origin: EP0567092A2] A rig for a sailboat is described, consisting of a mast (3) firmly connected to the vessel (2) and of a sail (1) which, as an aerodynamic propulsion and lift surface, is mounted in such a way as to be pivotable, tiltable and rotatable about the longitudinal, transverse and vertical axis. According to the invention, provision is made for the sail (1) to be connected on a sail spar (6) with linear guidance via a linear bearing (19) and a pivot bearing (7) to the mast (3) in such a way that it is pivoted via the same to the respective lee side of the vessel (2) and is lowered there on account of its own weight. The aerodynamic pressure point is therefore always located below the longitudinal axis of the pivot bearing (7). The sail (1) lifts automatically when the wind increases and thus exerts a lifting action on the entire sailboat. <IMAGE>

IPC 1-7

**B63H 9/06**

IPC 8 full level

**B63H 9/06** (2006.01)

CPC (source: EP)

**B63H 9/068** (2020.02)

Citation (search report)

- [A] DE 3222756 A1 19831222 - HAMANN GEORG
- [A] CH 674730 A5 19900713 - MARC DERIAZ, et al
- [A] FR 2498554 A1 19820730 - BURGARD FRANCK [FR]

Cited by

DE19512948A1; US6562749B1; WO2007031851A1

Designated contracting state (EPC)

AT BE CH DE DK FR GB IT LI NL

DOCDB simple family (publication)

**EP 0567092 A2 19931027; EP 0567092 A3 19940406**; DE 4213467 A1 19931104; DE 4213467 C2 19950427

DOCDB simple family (application)

**EP 93106458 A 19930421**; DE 4213467 A 19920424