

Title (en)
Reamer.

Title (de)
Räumvorrichtung.

Title (fr)
Alesoir.

Publication
EP 0568292 A1 19931103 (EN)

Application
EP 93303215 A 19930423

Priority
GB 9209008 A 19920425

Abstract (en)
The present invention provides a reamer 1 suitable for use in pipework 2 having at least two different internal diameters in a section thereof. The reamer 1 comprises an elongate body 4 formed and arranged for passing through a reduced diameter portion of said pipework 2 and has cutting member supports 6 with fixed pivotal mountings for a cutting member 8 for pivotal movement thereof between a retracted position and a deployed position extending radially outwardly of the body 4. The body 4 also has cutting member drive means 10 which engages part 22 of the cutting member 8 for displacement of the cutting member 8 between its retracted and deployed positions and substantially securely supporting the cutting member 8 in its deployed condition against angular displacement in the plane of pivotal movement about the pivotal mounting means. <IMAGE>

IPC 1-7
E21B 37/02; **E21B 10/32**

IPC 8 full level
B08B 9/04 (2006.01); **E21B 10/32** (2006.01); **E21B 37/02** (2006.01)

CPC (source: EP)
B08B 9/0436 (2013.01); **B08B 9/045** (2013.01); **E21B 37/02** (2013.01)

Citation (search report)
• [X] US 4809793 A 19890307 - HAILEY CHARLES D [US]
• [X] US 2756968 A 19560731 - VINCENT EMANUEL, et al
• [X] US 4838354 A 19890613 - JENKINS ROBERT L [US]
• [A] US 3351144 A 19671107 - PARK ROBERT O
• [A] US 5036921 A 19910806 - PITTARD FRED J [US], et al

Cited by
EP2283201A4; CN113969764A; GB2391884A; GB2391884B; GB2471751A; GB2471751B; US8068616B2; US7933420B2; US6758275B2; US7950450B2; WO9917885A1; US8340318B2; US6886633B2; US6929076B2; US8327954B2; US8893826B2

Designated contracting state (EPC)
DE DK FR GB IT NL

DOCDB simple family (publication)
EP 0568292 A1 19931103; GB 9209008 D0 19920610; NO 931505 D0 19930423; NO 931505 L 19931026

DOCDB simple family (application)
EP 93303215 A 19930423; GB 9209008 A 19920425; NO 931505 A 19930423