

Publication

EP 0570854 A3 19940406

Application

EP 93107850 A 19930513

Priority

DE 4216939 A 19920522

Abstract (en)

[origin: EP0570854A2] A milling container 11 and an agitator shaft 14 arranged therein bound a milling space 15 which is partially filled with grinding bodies 19 and through which a charging suspension is moved axially. The dynamic separation of the grinding bodies consists of a rotating separating disc 24 in which screens 30 are fitted, preferably arranged perpendicularly with respect to the axial flow 28 of material for milling, and of an annular gap 27. This combination permits very small grinding bodies 19 to be used in an operationally reliable fashion accompanied by high flow rates and viscosities and low wear. Additionally, the seal 33 which is usually required is protected against grinding bodies 19 and the screens 30 can be easily reached for cleaning or replacement if openings are provided, as can be seen from Fig. 1, in the annular flange 25 which forms the fixed counterface of the annular gap 27.

IPC 1-7

B02C 17/16

IPC 8 full level

B02C 17/16 (2006.01)

CPC (source: EP)

B02C 17/161 (2013.01)

Citation (search report)

- [YD] DE 1482391 B1 19700820 - DRAISWERKE GMBH
- [Y] GB 2002653 A 19790228 - BUEHLER AG GEB
- [Y] DE 1507493 A1 19710701 - DRAISWERKE GMBH
- [A] EP 0260604 A2 19880323 - NETZSCH MASCHINENFABRIK [DE]
- [AD] DE 3437866 A1 19860417 - BASF FARBEN & FASERN [DE]
- [Y] SOVIET PATENTS ABSTRACTS Section PQ Week 8527, 15 August 1985 Derwent World Patents Index; Class P41, AN 85-164367

Cited by

EP0771591A4; CN103240154A; CN117960316A

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

EP 0570854 A2 19931124; EP 0570854 A3 19940406; DE 4216939 A1 19931125; DE 4216939 C2 19950126

DOCDB simple family (application)

EP 93107850 A 19930513; DE 4216939 A 19920522