

Title (en)

Method for preventing a stop streak in a jet loom.

Title (de)

Verfahren zum Vermeiden von Stopstreifen in einer Luftdüsenwebmaschine.

Title (fr)

Méthode pour empêcher une marque d'arrêt dans un métier à tisser à air.

Publication

EP 0572350 A1 19931201 (EN)

Application

EP 93810334 A 19930506

Priority

JP 11637092 A 19920508

Abstract (en)

To provide a method of preventing a stop streak caused by beating a faulty weft in a jet loom. STRUCTURE A weft (Y) ejected from a weft inserting main nozzle (19) is assisted by air jets issued from a plurality of auxiliary nozzles (20-23) in flying throughout a warp shed. A plurality of weft arrival detectors (F1-F7) are arranged at spaced intervals between any paired auxiliary nozzles and also between any two adjacent pairs of such nozzles. If a control computer (C) fails to receive a weft arrival signal from any of the weft arrival detectors (F1-F7) later than the latest permissible arrival time, it causes a loom drive motor (M) to be stopped immediately with simultaneous application of brake (B). <IMAGE>

IPC 1-7

D03D 47/30

IPC 8 full level

D03D 51/34 (2006.01); **D03D 47/30** (2006.01); **D03D 51/00** (2006.01)

CPC (source: EP)

D03D 47/30 (2013.01); **D03D 47/3073** (2013.01); **D03D 51/002** (2013.01); **D03D 51/34** (2013.01)

Citation (search report)

- [Y] EP 0229432 A2 19870722 - TSUDAKOMA IND CO LTD [JP]
- [Y] EP 0207470 A2 19870107 - NISSAN MOTOR [JP]
- [A] CH 668997 A5 19890215 - ZELLWEGER USTER AG
- [AD] DATABASE WPI Section Ch, Week 8749, 31 October 1987 Derwent Publications Ltd., London, GB; Class F02, AN 87-345766

Cited by

CN109943957A; EP0743384A3; CN105420895A; EP3348688A1; CN108301105A

Designated contracting state (EPC)

BE DE FR IT

DOCDB simple family (publication)

EP 0572350 A1 19931201; JP 3170863 B2 20010528; JP H05321096 A 19931207

DOCDB simple family (application)

EP 93810334 A 19930506; JP 11637092 A 19920508