

Title (en)

Shaft furnace taphole piercing machine

Title (de)

Schachtofenabstichmaschine

Title (fr)

Machine de perçage d'un trou de coulée d'un four à cuve

Publication

EP 0574729 B1 19981202 (FR)

Application

EP 93108260 A 19930521

Priority

- LU 88135 A 19920617
- LU 88167 A 19920902

Abstract (en)

[origin: GB2267956A] A machine by which a rod (54) is driven into taphole clay, before it has fully hardened, and is later extracted to open the taphole, comprises a mounting, a carriage (32) which can be displaced along this mounting and a drive means for the carriage (32). Guide means (68, 70) define a guide channel (64) for the rod and have a longitudinal opening (78) giving access to inside the guide channel (64), perpendicularly to its axis. A finger (42) penetrates through the said longitudinal opening (78) to inside the said guide channel (64) to exert an axial thrust on one end of the piercing rod (54). <IMAGE>

IPC 1-7

C21B 7/12

IPC 8 full level

C21B 7/12 (2006.01)

CPC (source: EP US)

C21B 7/12 (2013.01 - EP US)

Designated contracting state (EPC)

BE ES FR IT NL SE

DOCDB simple family (publication)

EP 0574729 A1 19931222; EP 0574729 B1 19981202; AU 3996193 A 19931223; AU 656472 B2 19950202; CA 2098564 A1 19931218; CN 1036209 C 19971022; CN 1083114 A 19940302; CZ 106693 A3 19940119; CZ 283022 B6 19971217; DE 4317436 A1 19931223; DE 4317436 C2 20020718; ES 2125929 T3 19990316; GB 2267956 A 19931222; GB 2267956 B 19960103; GB 9310794 D0 19930714; JP H0688111 A 19940329; KR 100253683 B1 20000415; PL 172793 B1 19971128; PL 299365 A1 19940110; RU 2094469 C1 19971027; SK 59693 A3 19940112; US 5351939 A 19941004

DOCDB simple family (application)

EP 93108260 A 19930521; AU 3996193 A 19930602; CA 2098564 A 19930616; CN 93106989 A 19930616; CZ 106693 A 19930603; DE 4317436 A 19930526; ES 93108260 T 19930521; GB 9310794 A 19930525; JP 17120193 A 19930616; KR 930010643 A 19930611; PL 29936593 A 19930617; RU 93049640 A 19930616; SK 59693 A 19930610; US 8014593 A 19930617