

Title (en)

Method and device for starting and stopping the sheet reversal during sheet feeding through a printing machine

Title (de)

Verfahren und Einrichtung zum An- und Abstellen der Bogenwendung bei der Förderung von Bogen durch eine Druckmaschine

Title (fr)

Procédé et dispositif pour la mise en/hors service du dispositif de retournement des feuilles lors de l'alimentation en feuilles dans une machine à imprimer

Publication

EP 0579002 B1 19971112 (DE)

Application

EP 93109982 A 19930623

Priority

DE 4223190 A 19920715

Abstract (en)

[origin: EP0579002A1] 2.1. The invention is intended to achieve the object of implementing the starting and stopping of the sheet reversal using simple means of printing technology, it being possible for short reversal times to be achieved. 2.2. The invention consists in the fact that the adjustment of the phase position of the printing units, of the points in time of the opening of the grippers and of the elements (10, 11) holding the leading edge and trailing edge of the sheets takes place essentially simultaneously. For this purpose, the device comprises pressure medium-actuated couplings (46, 47, 49, 68, 69, 73) and further pressure medium-actuated actuators, the associated operating cylinders (31, 49, 63, 69, 104, 124) being arranged fixed to the frame. 2.3. The invention is applicable in sheet-fed printing machines with a device for sheet reversal. <IMAGE>

IPC 1-7

B41F 21/10

IPC 8 full level

B41F 21/10 (2006.01); **B41F 33/06** (2006.01)

CPC (source: EP US)

B41F 21/106 (2013.01 - EP US)

Designated contracting state (EPC)

CH DE FR GB IT LI

DOCDB simple family (publication)

EP 0579002 A1 19940119; **EP 0579002 B1 19971112**; DE 4223190 A1 19940120; DE 4223190 C2 19951207; DE 59307659 D1 19971218; JP 3331239 B2 20021007; JP H06155713 A 19940603; US 5365845 A 19941122

DOCDB simple family (application)

EP 93109982 A 19930623; DE 4223190 A 19920715; DE 59307659 T 19930623; JP 17425093 A 19930714; US 9196693 A 19930715