

Title (en)

PRESS INSTALLATION

Publication

**EP 0581008 A3 19940511 (DE)**

Application

**EP 93109676 A 19930617**

Priority

DE 4221147 A 19920627

Abstract (en)

[origin: EP0581008A2] In order to bring about a considerable decrease in investment and operating costs in the case of a press installation having a press frame composed of press stands (2), a press table (5) and a headpiece (1), the press parts being rigidly connected to one another by means of clamping tie elements (4); having pusher rods (7) for deformation; and having a transfer device (14, 15, 16) for transferring the workpieces between work stages (13, 6) and drive means (19, 20) for imparting movement to the pusher rod (7) and the transfer device (14, 15, 16), a combination of the following characteristics is proposed: - a pusher rod (7) extends over a plurality of work stages (6). - The pusher rod (7) is articulated without centres of pressure, and therefore directly, at four points (18) by means of connecting rods (17). - The centres of the two articulation points (18) in each case of one side of the pusher rod and of two clamping tie elements (4) which are situated opposite one another in the press frame are arranged on a common line (21) which is aligned horizontally and perpendicularly to the pressing path (35). - Inner pusher rods (8) are mounted so as to be vertically displaceable in the number of work stages (6) via guides (24), in the pusher rod (7) which takes the form of an outer pusher rod. - Between each of the inner pusher rods (8) and the outer pusher rod (7) there is arranged in each case at least one overload protection device (25) having a pressure chamber (28) in a pressure cylinder (27) and a piston (29). - The pressure chamber (28) is preloaded with pressure via pipes (33) so as to load the piston (29) and therefore the inner pusher rod (8) vertically downwards, to permit operation of the pressing installation. <IMAGE>

IPC 1-7

**B30B 15/06; B21D 35/00; B21D 43/05; B21D 37/08**

IPC 8 full level

**B21D 35/00** (2006.01); **B21D 37/08** (2006.01); **B21D 43/05** (2006.01); **B30B 1/26** (2006.01); **B30B 15/00** (2006.01); **B30B 15/04** (2006.01);  
**B30B 15/06** (2006.01); **B30B 15/28** (2006.01)

CPC (source: EP US)

**B21D 35/00** (2013.01 - EP US); **B21D 37/08** (2013.01 - EP US); **B21D 43/05** (2013.01 - EP US); **B30B 1/265** (2013.01 - EP US);  
**B30B 15/0035** (2013.01 - EP US); **B30B 15/04** (2013.01 - EP US); **B30B 15/065** (2013.01 - EP US); **B30B 15/284** (2013.01 - EP US)

Citation (search report)

- [Y] GB 1161526 A 19690813 - WEINGARTEN AG MASCHF [DE]
- [A] FR 2640895 A1 19900629 - MUELLER WEINGARTEN MASCHF [DE]
- [AD] EP 0388610 A1 19900926 - SCHULER GMBH L [DE]
- [A] US 3902347 A 19750902 - RIDGWAY MERRILL L, et al
- [Y] PATENT ABSTRACTS OF JAPAN vol. 9, no. 168 (M-396)(1891) 13. Juli 1985 & JP-A-60 040 700 ( HITACHI ZOSEN KK ) 4. März 1985

Cited by

EP0888874A3; CN102712159A; EP0628404A1; EP0637508A1; US5582063A; EP0628363A1; US5551275A; CN106040843A; US8944801B2

Designated contracting state (EPC)

DE ES FR GB IT SE

DOCDB simple family (publication)

**EP 0581008 A2 19940202; EP 0581008 A3 19940511; EP 0581008 B1 19961127**; CZ 125393 A3 19941019; CZ 282708 B6 19970917;  
DE 4221147 A1 19940105; DE 59304577 D1 19970109; DE 59310259 D1 20020314; EP 0722793 A2 19960724; EP 0722793 A3 19970319;  
EP 0722793 B1 20020123; ES 2096144 T3 19970301; ES 2169772 T3 20020716; US 5375513 A 19941227

DOCDB simple family (application)

**EP 93109676 A 19930617**; CZ 125393 A 19930623; DE 4221147 A 19920627; DE 59304577 T 19930617; DE 59310259 T 19930617;  
EP 96104634 A 19930617; ES 93109676 T 19930617; ES 96104634 T 19930617; US 8078393 A 19930624