

Title (en)

Method and apparatus for transferring a panty from a panty sewing machine to a toe closing sewing machine

Title (de)

Verfahren und Vorrichtung zum Überführen einer Strumpfhose von einer Strumpfhosen-Nähmaschine zu einer zehenschliessenden Nähmaschine

Title (fr)

Procédé pour le transfert d'un collant d'une machine à coudre les collants à une machine à coudre les pointes et un dispositif pour sa mise en oeuvre

Publication

EP 0584050 B1 19960522 (FR)

Application

EP 93830321 A 19930723

Priority

IT FI920164 A 19920805

Abstract (en)

[origin: EP0584050A1] To transfer a pair of tights (1) from a machine for sewing tights to a machine for sewing the toes (90), use is made of an apparatus comprising: - means (200) arranged below the rail (2) of the machine for sewing tights, in order to draw downwards the legs (100) of the pair of tights (1) which hang from the said rail (2), with a retractable tube (25) connected to a suction device; - movable gripper means (16) for slipping off the elastic edge (30) of the body (3) from the form (4) of the machine for sewing tights and for extending it horizontally; - means for spreading vertically the body (3) of the pair of tights (1) which has been slipped off from the said forms (14), with two twin hooks (6) capable of being spread apart vertically and subjected to an alternating horizontal movement synchronised with the said gripper (16); - means for extracting the body (3) of the pair of tights (1) from the said hooks (6) and for slipping it on to the tubes (9) of the machine for sewing the toes (90), by overturning it, with two parallel and spaced hooks (62) subjected to an alternating horizontal movement and arranged parallel and on each side of the abovementioned tubes (9); - means for spreading the legs (100) of the pair of tights (1) which have been tensioned and for bringing the toes of their feet (102) near to the mouth of the said tubes (9), with a plate (8) having a W-shaped profile, supported by a vertical arm (7) fastened to a carriage (70) sliding on a rectilinear guide rail (71) having an axis (a) inclined upwards. <IMAGE>

IPC 1-7

D05B 23/00

IPC 8 full level

D05B 21/00 (2006.01); **A41B 11/14** (2006.01); **D05B 23/00** (2006.01)

CPC (source: EP US)

D05B 23/007 (2013.01 - EP US)

Designated contracting state (EPC)

DE ES FR GB IT

DOCDB simple family (publication)

EP 0584050 A1 19940223; EP 0584050 B1 19960522; CA 2101583 A1 19940206; CN 1089457 A 19940720; DE 69302778 D1 19960627; IT 1258180 B 19960220; IT FI920164 A0 19920805; IT FI920164 A1 19940205; JP 2649478 B2 19970903; JP H06200402 A 19940719; RU 2089687 C1 19970910; US 5373977 A 19941220

DOCDB simple family (application)

EP 93830321 A 19930723; CA 2101583 A 19930729; CN 93109268 A 19930805; DE 69302778 T 19930723; IT FI920164 A 19920805; JP 21338293 A 19930805; RU 93048873 A 19930804; US 8642593 A 19930630