

Title (en)

PRESS WITH A HYDRAULIC DRIVE, IN PARTICULAR A SHEET-SHAPING PRESS

Title (de)

PRESSE MIT EINEM HYDRAULISCHE ANTRIEB, INSBESONDERE EINE BLECHFORMPRESSE

Title (fr)

PRESSE AVEC UNE COMMANDE HYDRAULIQUE, NOTAMMENT UNE PRESSE A FORMER LES TOLES

Publication

**EP 0586669 B1 19980218 (DE)**

Application

**EP 93907756 A 19930325**

Priority

- DE 9300275 W 19930325
- DE 4210053 A 19920327
- DE 4218954 A 19920610

Abstract (en)

[origin: DE4309641A1] The first hydrostatic machine (30) is an axial piston assembly and alternately works on both sides for regulating pressure. During the return stroke of the holder (17), the pressure medium flows out of the hydraulic cylinder (21) through a second hydrostatic machine (70). The second hydrostatic machine is driven as a hydro motor during the return stroke and expels the pressure medium from the hydraulic cylinder. The first hydrostatic machine is provided with load dependent control which controls the pressure regulation. ADVANTAGE - Power is saved by using the pressure of the pressure medium flowing from the cylinder.

IPC 1-7

**B21D 24/14**

IPC 8 full level

**B21D 24/08** (2006.01); **B21D 24/14** (2006.01)

CPC (source: EP US)

**B21D 24/08** (2013.01 - EP US); **B21D 24/14** (2013.01 - EP US); **B30B 1/266** (2013.01 - EP US); **B30B 15/16** (2013.01 - EP US)

Cited by

DE102021209477B4

Designated contracting state (EPC)

DE ES FR IT SE

DOCDB simple family (publication)

**DE 4309641 A1 19930930**; CZ 226293 A3 19960612; CZ 281492 B6 19961016; DE 59308158 D1 19980326; EP 0586669 A1 19940316; EP 0586669 B1 19980218; ES 2114044 T3 19980516; JP H06510949 A 19941208; US 5499525 A 19960319; WO 9319866 A1 19931014

DOCDB simple family (application)

**DE 4309641 A 19930325**; CZ 226293 A 19930325; DE 59308158 T 19930325; DE 9300275 W 19930325; EP 93907756 A 19930325; ES 93907756 T 19930325; JP 51696893 A 19930325; US 14249094 A 19940520