

Title (en)

Device for engaging and disengaging the inking unit drive and the dampening unit drive

Title (de)

Einrichtung zum Ein- und Auskuppeln von Farb- und Feuchtwerkantrieb

Title (fr)

Dispositif pour embrayer et déembrayer l'entraînement du dispositif d'encre et du dispositif de mouillage

Publication

**EP 0588188 B1 19961211 (DE)**

Application

**EP 93114202 A 19930904**

Priority

DE 4230937 A 19920916

Abstract (en)

[origin: EP0588188A1] The invention relates to a device for engaging and disengaging the inking unit drive and the damping unit drive on rotary printing machines and comprises the features described below. A control hub (13), which is mounted in a freely accessible manner on at least one printing unit (1), can be switched into a plurality of catch positions (I, II, III). A securing movement of the control hub (13), which precedes a switching movement of the control hub (13), can be detected via a sensor system (16). A control shaft (11) is provided with a cam piece (12) whose profile is scanned continuously by scanning devices (17, 18). The switching movement of the control hub (13) is converted by transmission elements (9, 10) into an axial movement of a slide bush (3). <IMAGE>

IPC 1-7

**B41F 31/00**; **B41F 33/10**; **B41F 7/26**

IPC 8 full level

**B41F 7/26** (2006.01); **B41F 31/00** (2006.01); **B41F 33/10** (2006.01)

CPC (source: EP US)

**B41F 7/26** (2013.01 - EP US); **B41F 31/004** (2013.01 - EP US); **B41F 33/10** (2013.01 - EP US)

Designated contracting state (EPC)

AT CH DE FR GB LI NL

DOCDB simple family (publication)

**EP 0588188 A1 19940323**; **EP 0588188 B1 19961211**; AT E146131 T1 19961215; DE 4230937 A1 19940317; DE 59304731 D1 19970123; US 5353702 A 19941011

DOCDB simple family (application)

**EP 93114202 A 19930904**; AT 93114202 T 19930904; DE 4230937 A 19920916; DE 59304731 T 19930904; US 12276393 A 19930916