

Title (en)

PROCESS FOR PRODUCING A READY-TO-USE STRING FOR RACQUETS, ESPECIALLY TENNIS RACQUETS.

Title (de)

VERFAHREN ZUM HERSTELLEN EINER BESPANNUNGSSAITE IN LIEFERFORM FÜR BALLSCHLÄGER, INSBESONDERE TENNISSCHLÄGER.

Title (fr)

PROCEDE DE FABRICATION D'UNE CORDE DE MISE EN TENSION PRETE A L'EMPLOI POUR RAQUETTES, NOTAMMENT POUR RAQUETTES DE TENNIS.

Publication

EP 0589010 B1 19951102 (DE)

Application

EP 93907636 A 19930407

Priority

- AT 9300063 W 19930407
- AT 74792 A 19920409

Abstract (en)

[origin: WO9320903A1] In a process for conditioning a string for tennis racquets, the latter is wound on a spool (1) under tension producing an extension of 5 to 15% in the string. To this end, a length of raw string (19) is drawn off a supply drum (20) and its end (6) is secured to the periphery of the spool (1) which is then moved away from the supply drum (20) so that the raw string (19) is drawn off the supply drum (20) to the length to be wound. The length of raw string drawn off is then subjected to tension imparting a predetermined extension whereupon, with the tension maintained, the extended string length (7) is wound on the spool (1) with the latter moved at the same time towards the supply drum (20) and finally the other end of said length of string (7) is secured to the periphery of the spool (1).

IPC 1-7

A63B 51/02; **D07B 7/10**

IPC 8 full level

A63B 51/02 (2015.01); **B65H 75/28** (2006.01); **D07B 7/10** (2006.01)

CPC (source: EP US)

A63B 51/02 (2013.01 - EP US); **B65H 75/28** (2013.01 - EP US)

Designated contracting state (EPC)

AT BE CH DE ES FR GB IT LI LU NL PT SE

DOCDB simple family (publication)

WO 9320903 A1 19931028; AT 400002 B 19950925; AT A74792 A 19950115; AT E129646 T1 19951115; AU 3817493 A 19931118; DE 59300851 D1 19951207; EP 0589010 A1 19940330; EP 0589010 B1 19951102; ES 2079970 T3 19960116; JP H06508542 A 19940929; US 5454525 A 19951003

DOCDB simple family (application)

AT 9300063 W 19930407; AT 74792 A 19920409; AT 93907636 T 19930407; AU 3817493 A 19930407; DE 59300851 T 19930407; EP 93907636 A 19930407; ES 93907636 T 19930407; JP 51783993 A 19930407; US 15708393 A 19931207