

Title (en)
Fastener.

Title (de)
Verschluss.

Title (fr)
Fermoir.

Publication
EP 0590207 A1 19940406 (EN)

Application
EP 92308831 A 19920928

Priority
EP 92308831 A 19920928

Abstract (en)

A fastener arrangement designed for releasably fastening a first means to a second means is described. The fastener comprises cooperating male (A-1) and female (B-1) members which are mounted respectively on the first and second means. The male member (A-1) has a projection (E) formed of or incorporating a permanent magnet (1) and having both a shank (2) and a head portion (2a) which overhangs the shank on at least one side of it. The female member (B-1) comprises a frame (F) having an opening which receives the projection (E) of the male member. A slide member (5) is slidably received within the frame (F) and is capable of manipulation from the exterior of the frame to release the fastener. The slide member (5) has an opening (8) which can be brought into confronting relation with the frame opening so that the projection (E) can be inserted through the frame opening and the slide opening at the same time. The slide member (5) is formed from ferromagnetic material and so is magnetically attracted to a shank (2) of the projection when inserted. As a result, the head portion (2a) of the projection (E) is entrapped beyond the slide opening by the slide member (5) engaging the shank beneath the overhang and as a result preventing retraction of the projection. The frame member (F) is formed from first (3) and second (4) generally parallel plate members each having an opening for the projection (E). The plate members (3,4) are spaced sufficiently to accommodate the slide member (5) between them. The frame (F) is completed by side members (3a) integral with one of the plate members. Side edges of the other plate member (4) and the corresponding edges of the side members (3a) have complementary configurations of projected and intended portions which interengage. The projected portions formed either on the edges of the side members (3a) or on the side edges of the other plate member (4) are deformed to firmly hold these edges interengaged and as a result to hold the plate members together to form the frame. <IMAGE>

IPC 1-7
A44B 11/25; **A45C 13/10**; **E05C 19/16**; **H01F 7/02**

IPC 8 full level
A41F 1/00 (2006.01); **A45C 13/10** (2006.01); **E05C 19/16** (2006.01); **H01F 7/02** (2006.01)

CPC (source: EP)
A41F 1/002 (2013.01); **A45C 13/1069** (2013.01); **E05C 19/163** (2013.01); **H01F 7/0263** (2013.01); **A44D 2203/00** (2013.01)

Citation (search report)

- [XD] JP H0314983 B2 19910228
- [Y] FR 2397050 A1 19790202 - APPLIC ART LAB CO [JP]
- [Y] US 1465578 A 19230821 - CAROLIN JAMES B
- [A] US 2475226 A 19490705 - ELLIS ROBERT P
- [A] US 2856221 A 19581014 - AIME ORCEL
- [A] PATENT ABSTRACTS OF JAPAN vol. 16, no. 173 (M-1240)24 April 1992 & JP-A-4 016 684 (TAAMO KK) 21 January 1992

Cited by
IT201700067329A1; EP0970628A3; EP0838173A3; EP0662290A3; US11089844B2; WO2018229637A1; EP2043475B1

Designated contracting state (EPC)
AT BE CH DE DK ES FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)
EP 0590207 A1 19940406; **EP 0590207 B1 19971210**; AT E160920 T1 19971215; DE 69223513 D1 19980122; DE 69223513 T2 19980604

DOCDB simple family (application)
EP 92308831 A 19920928; AT 92308831 T 19920928; DE 69223513 T 19920928