

Title (en)

Cleaning device for a cylinder of a printing machine

Title (de)

Druckmaschinezylinder-Waschvorrichtung

Title (fr)

Dispositif de nettoyage pour cylindre de machine à imprimer

Publication

**EP 0591634 B1 19960424 (DE)**

Application

**EP 93111383 A 19930715**

Priority

DE 4233953 A 19921008

Abstract (en)

[origin: EP0591634A1] A cleaning device of a cylinder of a printing machine for washing at least one cylinder (2) in the printing unit of a printing machine. A washing beam (6) is supported by a suspension device (20) and can be moved by the latter between a washing position near to the cylinder surface and a starting position further away from the cylinder surface. The washing beam (6) is connected to the suspension device (20) by means of a linear guide device (24) by means of which, in the starting position, the washing beam (6) can be extended from or retracted into the suspension device and the printing unit in the longitudinal direction of the washing beam. Connection means (28) of the washing beam (6) are automatically coupled to or uncoupled from a connection unit (36) during linear displacement of the washing beam (6) in order to feed washing liquid and compressed air to the washing beam (6) in the coupled state. <IMAGE>

IPC 1-7

**B41F 35/00**

IPC 8 full level

**B41F 35/00** (2006.01)

CPC (source: EP)

**B41F 35/00** (2013.01)

Cited by

DE10000554A1; DE19860855A1; DE19506640A1; EP0728582A3; US5615612A; DE19506640C2; US7506585B2; US6601510B1

Designated contracting state (EPC)

CH DE FR GB IT LI SE

DOCDB simple family (publication)

**EP 0591634 A1 19940413; EP 0591634 B1 19960424**; DE 4233953 A1 19940414; DE 59302344 D1 19960530

DOCDB simple family (application)

**EP 93111383 A 19930715**; DE 4233953 A 19921008; DE 59302344 T 19930715