

Title (en)

Device for winding at least one synthetic thread.

Title (de)

Vorrichtung zum Aufspulen mindestens eines synthetischen Fadens.

Title (fr)

Dispositif pour bobiner au minimum un fil synthétique.

Publication

EP 0591824 A3 19950719 (DE)

Application

EP 93115690 A 19930929

Priority

DE 4233638 A 19921006

Abstract (en)

[origin: EP0591824A2] The invention relates to a device for winding at least one synthetic thread, especially on a stretch-winding machine with a rotatable bobbin tube 1, with a driven friction roller 3 touching the outer circumference of the bobbin tube 1, with a traversing device 4 for the synthetic thread 5 and with a collar 6 rotating synchronously with the bobbin tube 1 and having a larger diameter than the bobbin tube. According to the invention, the collar 6 is arranged next to the friction casing of the friction roller 3 and is designed for receiving the initial length of the synthetic thread, the bobbin tube 1 being assigned a thread-guide device 8 for guiding the thread 5 running onto the collar 6 into the region of the bobbin tube 1. <IMAGE>

IPC 1-7

B65H 54/42

IPC 8 full level

B65H 54/34 (2006.01); **B65H 54/42** (2006.01)

CPC (source: EP US)

B65H 54/34 (2013.01 - EP US); **B65H 54/42** (2013.01 - EP US); **B65H 2701/31** (2013.01 - EP US)

Citation (search report)

- [XY] CH 449491 A 19671231 - HOECHST AG [DE]
- [YA] FR 2284550 A1 19760409 - RIETER AG MASCHF [CH]
- [YA] US 4085901 A 19780425 - SANDERS JAMES E
- [YA] DE 7715777 U1 19770901
- [X] FR 2552746 A1 19850405 - SAURER ALLMA GMBH [DE]
- [A] FR 2268739 A1 19751121 - RIETER AG MASCHF [CH]
- [A] DE 7322686 U
- [XA] PATENT ABSTRACTS OF JAPAN vol. 4, no. 158 (M - 39)<640> 5 November 1980 (1980-11-05)

Designated contracting state (EPC)

CH DE FR IT LI

DOCDB simple family (publication)

EP 0591824 A2 19940413; EP 0591824 A3 19950719; EP 0591824 B1 19970625; DE 4233638 A1 19940407; DE 59306817 D1 19970731; JP H06191725 A 19940712; US 5465916 A 19951114

DOCDB simple family (application)

EP 93115690 A 19930929; DE 4233638 A 19921006; DE 59306817 T 19930929; JP 23654893 A 19930922; US 12884693 A 19930929