

Title (en)

Machine and method for drying sheets of wood obtained by slicing, rotary cutting and the like.

Title (de)

Maschine und Verfahren zur Trocknung von Holzplatten hergestellt durch flaches oder rotierendes Abschneiden oder dergleichen.

Title (fr)

Appareil et procédé pour le séchage de feuilles de bois obtenues par découpage rotatif ou analogue.

Publication

EP 0592752 A1 19940420 (EN)

Application

EP 92830573 A 19921016

Priority

EP 92830573 A 19921016

Abstract (en)

A dryer for sliced or peeled sheets of wood and the like, characterised in that it includes two or more superimposed or superimposable rigid plates (5), the facing and opposing surfaces of which are substantially flat; spacer means (6) interposed or interposable between the plates so as to define between facing surfaces of the plates at least one interspace (7) of uniform height for receiving the sheets of wood (A) to be dried, a heat source (8) for supplying the plates with the thermal energy necessary to dry the wood; the height of the spacer means being just sufficient to prevent the plates from squashing the wood while allowing the sheets of wood to shrink freely in their own planes, parallel to the faces of the plates, as a result of the drying. <IMAGE>

IPC 1-7

F26B 3/20; **F26B 7/00**; **F26B 25/00**

IPC 8 full level

F26B 3/20 (2006.01); **F26B 5/04** (2006.01); **F26B 25/00** (2006.01)

CPC (source: EP)

F26B 3/20 (2013.01); **F26B 5/045** (2013.01); **F26B 25/004** (2013.01)

Citation (search report)

- [X] FR 62054 E 19550602
- [X] US 4811496 A 19890314 - HONDA NORIYUKI [JP], et al
- [A] DE 9101990 U1 19910508
- [A] DE 1191405 B 19650422 - SCHILDE MASCHB AG
- [A] DE 2904243 A1 19790816 - COMMW SCIENT IND RES ORG
- [A] DE 495236 C 19300404 - BECKER & VAN HUELLEN

Cited by

CN110595189A; CN100390482C; CN111536771A; FR2790648A1; WO2005054765A1

Designated contracting state (EPC)

DE ES FR GB

DOCDB simple family (publication)

EP 0592752 A1 19940420

DOCDB simple family (application)

EP 92830573 A 19921016