

Publication

EP 0601013 A4 19940803

Application

EP 92918287 A 19920821

Priority

- US 9207030 W 19920821
- US 74989791 A 19910826

Abstract (en)

[origin: WO9304541A1] A polled digital multiport, multidrop system is described. The inbound frame for sending information from remote terminals (42) to the host terminals (12) is arranged such that a plurality of bytes are provided by a first terminal, followed by a guard band, followed by a plurality of bytes provided by a second terminal, followed by another guard band, etc. The guard band permits signalling between the DSU (16, 36, 116) and the OCU (24), which in turn permits the OCU (24) to signal the MJU (28) that no data will be coming from the OCU (24). In this manner, control mode idle is accomplished and data mode idle is avoided. In addition, because of the guard band, if the delay from a remote site changes, no data will be lost. Means for monitoring the system (154) to follow changes in delay are also provided, and the system can cause a remote location to accommodate a change in delay.

IPC 1-7

H04J 3/14

IPC 8 full level

H04J 3/06 (2006.01); **H04J 3/12** (2006.01); **H04J 3/14** (2006.01); **H04J 3/16** (2006.01); **H04L 29/06** (2006.01)

CPC (source: EP)

H04J 3/0682 (2013.01); **H04J 3/12** (2013.01); **H04J 3/14** (2013.01); **H04J 3/16** (2013.01); **H04L 9/40** (2022.05)

Citation (search report)

- [A] GB 2232041 A 19901128 - AMERICAN TELEPHONE & TELEGRAPH [US]
- [A] PATENT ABSTRACTS OF JAPAN vol. 5, no. 171 (E - 080) 30 October 1981 (1981-10-30)
- See references of WO 9304541A1

Designated contracting state (EPC)

DE ES FR GB IT

DOCDB simple family (publication)

WO 9304541 A1 19930304; AU 2490792 A 19930316; AU 661864 B2 19950810; CA 2116228 A1 19930304; EP 0601013 A1 19940615; EP 0601013 A4 19940803

DOCDB simple family (application)

US 9207030 W 19920821; AU 2490792 A 19920821; CA 2116228 A 19920821; EP 92918287 A 19920821