

Title (en)

Golf ball and method of manufacturing the same.

Title (de)

Golfball sowie Verfahren zur Herstellung desselben.

Title (fr)

Balle de golf et son procédé de fabrication.

Publication

EP 0601861 A1 19940615 (EN)

Application

EP 93309922 A 19931209

Priority

JP 35254292 A 19921209

Abstract (en)

A golf ball has a surface uniformly covered with a paint coating so that the carrying properties of dimples can be stably elicited. A paint to which a voltage of more than 50,000 V is applied is supplied to a disc revolving at a speed of more than 15,000 rpm for atomization, the atomized paint being coated on the surface of the golf ball to form a paint coat within a thickness in the range of from 5 to 60 μm , with a maximum/minimum coat thickness ratio of 1 to 2. <IMAGE>

IPC 1-7

A63B 37/12; **B05B 5/04**

IPC 8 full level

A63B 37/00 (2006.01); **A63B 37/12** (2006.01); **A63B 37/14** (2006.01); **A63B 45/00** (2006.01); **B05B 5/04** (2006.01)

CPC (source: EP US)

A63B 37/00222 (2020.08 - EP US); **A63B 37/12** (2013.01 - EP); **A63B 45/00** (2013.01 - EP); **B05B 5/04** (2013.01 - EP)

Citation (search report)

- [XY] US 4802674 A 19890207 - KITAOH KATSUTOSHI [JP]
- [A] US 4871589 A 19891003 - KITAOH KATSUTOSHI [JP], et al
- [Y] PATENT ABSTRACTS OF JAPAN vol. 014, no. 363 (C - 0746) 7 August 1990 (1990-08-07)

Cited by

EP0911087A1; EP0661103A1; US5506004A; GB2290991A; GB2290991B; AU690271B2; US5789486A; WO0228485A3; US7687116B2; US7001286B2

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

EP 0601861 A1 19940615; **EP 0601861 B1 19970212**; AU 5219893 A 19940623; AU 676216 B2 19970306; DE 69308111 D1 19970327; DE 69308111 T2 19970605; JP H06170014 A 19940621

DOCDB simple family (application)

EP 93309922 A 19931209; AU 5219893 A 19931207; DE 69308111 T 19931209; JP 35254292 A 19921209