

Title (en)

MICRO-MINIATURISED, ELECTROSTATICALLY DRIVEN DIAPHRAGM MICROPUMP.

Title (de)

MIKROMINIATURISIERTE, ELEKTROSTATISCH BETRIEBENE MIKROMEMBRANPUMPE.

Title (fr)

MICROPOMPE MICROMINIATURISEE A MEMBRANE ET A COMMANDE ELECTROSTATIQUE.

Publication

EP 0603201 B1 19951115 (DE)

Application

EP 92916327 A 19920728

Priority

- DE 4130211 A 19910911
- DE 4135655 A 19911029
- DE 9200630 W 19920728

Abstract (en)

[origin: DE4143343A1] The electrostatic membrane pump has two pump blocks (2,3) of differing conductivity semiconductor materials, one of which provides a membrane zone (6) and each of which has a conductive electrode zone (11) coupled to a voltage source. The blocks (2,3) are relatively insulated from one another and together define a hollow space (10) adjacent the membrane zone (6), filled with a different fluid medium from that handled by the pump via an opening (4,5) in the pump block (2) opposite that incorporating the membrane zone (6). The opposing electrode zones (11) are arranged so that the fluid filling the hollow space (10) is subjected to the electrical field, but not the pumped fluid medium. USE - Accurate dosing of fluids in microlitre and sub-microlitre range.

IPC 1-7

F04B 43/04

IPC 8 full level

F04B 43/04 (2006.01); **F04B 53/10** (2006.01)

CPC (source: EP US)

F04B 43/046 (2013.01 - EP US); **F04B 53/1055** (2013.01 - EP US)

Designated contracting state (EPC)

CH DE FR GB LI NL

DOCDB simple family (publication)

DE 4143343 A1 19930325; DE 4143343 C2 19940922; DE 4135655 A1 19930318; DE 4135655 C2 19930805; DE 59204373 D1 19951221; EP 0603201 A1 19940629; EP 0603201 B1 19951115; KR 0119362 B1 19970930; US 5529465 A 19960625; WO 9305295 A1 19930318

DOCDB simple family (application)

DE 4143343 A 19911029; DE 4135655 A 19911029; DE 59204373 T 19920728; DE 9200630 W 19920728; EP 92916327 A 19920728; KR 19940700780 A 19940310; US 20426594 A 19940309