

Title (en)
Tile cutter

Title (de)
Fliessenschneidmaschine

Title (fr)
Dispositif à couper des carreaux

Publication
EP 0608476 B1 19981230 (EN)

Application
EP 93113611 A 19930825

Priority
IT VA930002 A 19930118

Abstract (en)

[origin: EP0608476A2] The end device comprises: a tool carrier (30), an operative station (11), a gauge (5) to maximize the distance from the contour line of the tile (0) to the pressure points, as well as the distance from the small roller (34) or fulcrum (f) to the push-operable scoring and cutting disc-like tool (3) or scoring weight arm which is of about 30 mm. Such fulcrum (f) engaging the bottom of the guide (2), which is placed parallel over base (1) 45 mm beyond the reaction apex (7). The power arm of the lever is 36 cm long. At parity of power arm, the weight arm is mm 90 long, whereby the pressers (4, 4') may operate at 100 mm far from the upright (10) or at least 22 mm from the contour line (0') and 32 mm inside the corner (0''). An adjuster means (38) limits the excursion of the pressers (4, 4') avoiding that the exceeding excursion thereof operates again accidentally on any of the already cut sections of the tile.

IPC 1-7

B28D 1/22; B28D 7/04

IPC 8 full level

B28D 1/22 (2006.01); **B28D 7/04** (2006.01)

CPC (source: EP)

B28D 1/225 (2013.01); **B28D 7/043** (2013.01)

Cited by

EP4219110A1; IT202200001715A1; US6148810A; GB2329144A; GB2329144B; WO2004030883A1

Designated contracting state (EPC)
AT DE ES FR GB IT PT

DOCDB simple family (publication)

EP 0608476 A2 19940803; EP 0608476 A3 19940824; EP 0608476 B1 19981230; AT E175144 T1 19990115; DE 69322848 D1 19990211;
DE 69322848 T2 20000629; ES 2128374 T3 19990516; IT 1265977 B1 19961216; IT VA930002 A0 19930118; IT VA930002 A1 19940718

DOCDB simple family (application)

EP 93113611 A 19930825; AT 93113611 T 19930825; DE 69322848 T 19930825; ES 93113611 T 19930825; IT VA930002 A 19930118