

Title (en)

Case with lock.

Title (de)

Behälter mit Verschluss.

Title (fr)

BÔîtier avec serrure.

Publication

EP 0613629 A2 19940907 (EN)

Application

EP 94102722 A 19940223

Priority

DE 9302674 U 19930224

Abstract (en)

A case lock for preferably locking a cover element with a base element comprises a projection at the base element with two recesses in its surface. A locking housing (2a) is arranged at the cover element which has a connecting passage and two openings in which bars (3) are arranged so that they can be spring-shifted against each other. A guidance of the bars (3) slides in each opening passage and a bar base in each opening. A bar element (3b) extends downwards with a claw being undercut so that the bar element can be engaged behind one of the recesses of the base element. Each bar (3) comprises a button which is adjacent outwards and/or forwards to the guidance and which operatively protrudes in the most relaxed spring position over the locking housing (2a) to such an extent that the claw (3c) grips behind the recess of the base element. In the spring-tensed condition the bars (3) are shiftable inwards at least to such an extent that the claw (3c) is disengaged with the recess at the base element. The bars are spaced about 10 to 80 mm apart from each other at the front side of the case so that they can be easily pressed together with, e.g., the thumb and the index finger of one hand. <IMAGE>

IPC 1-7

A45C 13/10; E05C 1/10; A45D 40/22

IPC 8 full level

A45C 13/10 (2006.01); **A45D 40/22** (2006.01)

CPC (source: EP)

A45C 13/10 (2013.01); **A45D 40/22** (2013.01)

Designated contracting state (EPC)

AT BE CH DE ES FR GB IT LI NL

DOCDB simple family (publication)

DE 9302674 U1 19930708; EP 0613629 A2 19940907; EP 0613629 A3 19941109

DOCDB simple family (application)

DE 9302674 U 19930224; EP 94102722 A 19940223