

Title (en)

Method and means of applying identification marks

Title (de)

Verfahren zum Anbringen von Kennzeichnungen und Kennzeichnungsmittel hierfür

Title (fr)

Méthode et moyenne pour l'application des marques distinctives

Publication

**EP 0616904 B1 19971112 (DE)**

Application

**EP 94104458 A 19940322**

Priority

DE 4309507 A 19930324

Abstract (en)

[origin: EP0616904A1] In a method for applying identification marks (10,16) on a sheetlike ground (12), the latter is provided with a base layer (18) of an adhesive which is or becomes transparent and then a pliant base web (14) which bears the mark (16) and whose format is at most that of the bed of adhesive (18) is pressed on, whereupon at least one further layer of adhesive (20) is applied with smoothing of the web (14) underneath. Preferably the web (14) has been lightly impregnated with a wet strength enhancer and is printed after it has dried with the mark (16) which is applied to the web (14) as a matter of choice in one or more colours and is heat-set thereon, for example 40 s at about 180°C. Of particular suitability is a paper web (14) having a basis weight below 25 g/m, a wall thickness of 10 to 500 µm, preferably 50 to 100 µm, and an average pore size of 100 to 300 µm, preferably 150 to 250 µm. The mark (16) consists of a very finely disperse, thinnable, light- and weather-resistant ink which has a solids content of not more than 20%.

IPC 1-7

**B44C 1/10; B44C 1/16; B41M 1/12; B41M 7/02**

IPC 8 full level

**B41M 1/12** (2006.01); **B41M 7/02** (2006.01); **B44C 1/10** (2006.01); **B44C 1/16** (2006.01)

CPC (source: EP)

**B41M 1/12** (2013.01); **B41M 7/02** (2013.01); **B44C 1/105** (2013.01); **B44C 1/16** (2013.01)

Cited by

CN1305013C; EP0868875A3

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB GR IE IT LI LU NL PT SE

DOCDB simple family (publication)

**EP 0616904 A1 19940928; EP 0616904 B1 19971112**; AT E160115 T1 19971115; DE 4309507 A1 19940929; DE 59404556 D1 19971218

DOCDB simple family (application)

**EP 94104458 A 19940322**; AT 94104458 T 19940322; DE 4309507 A 19930324; DE 59404556 T 19940322