

Title (en)
U-LOCK SECURITY SPACER.

Title (de)
U-FÖRMIGES BÜGELSCHLOSS MIT SICHERHEITS-ABSTANDSHALTER.

Title (fr)
SYSTEME ANTIVOL EN U DE TYPE CADENAS.

Publication
EP 0620889 A4 19950201 (EN)

Application
EP 92919426 A 19920903

Priority
• US 9207292 W 19920903
• US 75554691 A 19910905

Abstract (en)
[origin: WO9305258A1] A security spacer (24) is used with a U-lock (16) to provide additional security. The U-lock (16) includes a U-shaped bar (18) and a header (20). In certain circumstances, the arms of the U-lock (16) are sufficiently longer than the object (10) being locked that a gap (22) between the object (10) and header (20) is wide enough to allow a thief to insert a scissors jack between the arms and break the lock. The security spacer (24) substantially fills the gap to prevent the insertion of a jack and is held in place by the header (20). The security spacer (24) preferably includes two oval cylinders (26) connected at opposite ends of a metal bar (28).

IPC 1-7
E05B 67/38

IPC 8 full level
E05B 71/00 (2006.01); **B62H 5/00** (2006.01); **B62H 5/14** (2006.01); **E05B 67/38** (2006.01)

CPC (source: EP)
B62H 5/003 (2013.01); **B62H 5/14** (2013.01); **E05B 67/38** (2013.01)

Citation (search report)
• [X] AU 549021 B2 19860109 - KIRK I L, et al
• [X] GB 2185519 A 19870722 - LEE ROBERT, et al
• [X] US 4333326 A 19820608 - WINTERS ROBERT E
• See references of WO 9305258A1

Designated contracting state (EPC)
AT BE CH DE DK ES FR GB IE IT LI LU NL SE

DOCDB simple family (publication)
WO 9305258 A1 19930318; AU 2558492 A 19930405; BR 9206459 A 19951017; CA 2116961 A1 19930318; EP 0620889 A1 19941026; EP 0620889 A4 19950201; FI 941040 A0 19940304; FI 941040 A 19940304; JP H07501114 A 19950202

DOCDB simple family (application)
US 9207292 W 19920903; AU 2558492 A 19920903; BR 9206459 A 19920903; CA 2116961 A 19920903; EP 92919426 A 19920903; FI 941040 A 19940304; JP 50530493 A 19920903