

Title (en)

Rotary cylinder for a safety lock

Title (de)

Drehschliesszylinder für ein Sicherheitsschloss

Title (fr)

Cylindre rotatif pour serrure de sécurité

Publication

**EP 0626491 B1 19961227 (DE)**

Application

**EP 94810272 A 19940509**

Priority

CH 158893 A 19930527

Abstract (en)

[origin: EP0626491A1] A cutout (11) is made in a web (7) from above, a locking element (12) being inserted into said cutout. The cutout (11) connects an upper outer side of the web (7) to a transverse bore (9) in an arm (14) of the web (7). In the assembled state, the web (7) is inserted into a cutout (10) of the cylinder pocket (4) and connected by a transverse pin (6). In order to secure the transverse pin (6) against longitudinal displacement in the cylinder pocket (4), said transverse pin (6) exhibits an encircling groove (14) into which the locking element (12) engages from above. In order to exchange the web (7), the rotary cylinder (1) is rotated about its longitudinal axis such that the cylinder pocket (4) is at the top. Upon rotation, the locking element (12) moves downwards due to its gravitational force and releases the transverse pin (6). The rotary cylinder (1) according to the invention can be lengthened or shortened on site, without reducing the security, by exchanging the web (7). <IMAGE>

IPC 1-7

**E05B 9/10**

IPC 8 full level

**E05B 9/04** (2006.01); **E05B 9/10** (2006.01)

CPC (source: EP US)

**E05B 9/045** (2013.01 - EP US); **Y10T 70/7655** (2015.04 - EP US); **Y10T 70/8973** (2015.04 - EP US)

Cited by

AT539U3; EP1201852A3; DE29801490U1; EP0748908A3; AT405960B

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB GR IT LI LU NL PT SE

DOCDB simple family (publication)

**EP 0626491 A1 19941130; EP 0626491 B1 19961227**; AT E146843 T1 19970115; CA 2124285 A1 19941128; DE 59401377 D1 19970206; DK 0626491 T3 19970616; ES 2098114 T3 19970416; GR 3022921 T3 19970630; US 5501087 A 19960326

DOCDB simple family (application)

**EP 94810272 A 19940509**; AT 94810272 T 19940509; CA 2124285 A 19940525; DE 59401377 T 19940509; DK 94810272 T 19940509; ES 94810272 T 19940509; GR 970400607 T 19970326; US 23010494 A 19940420