

Title (en)

Stoplog device for retaining high water

Title (de)

Absperrvorrichtung zum Rückhalten von Hochwasser o. dgl.

Title (fr)

Dispositif d'obturation de retenue des crues

Publication

**EP 0627529 B1 19960904 (DE)**

Application

**EP 94108546 A 19940603**

Priority

- DE 4318274 A 19930603
- DE 4318275 A 19930603

Abstract (en)

[origin: EP0627529A1] A stop-log device for retaining high water or the like, with beam-like stop-log elements (2) which can be arranged one above the other in a horizontal position, are designed as hollow sections and engage at their ends in roughly U-shaped receptacles (1), seals (4) being provided between the bearing surfaces of the stop-log elements (2) and inside the receptacles (1). In order to be able to assemble the stop-log device simply, safely and quickly, extensions (5) in the longitudinal direction are provided at the end faces of the stop-log elements (2), and locking elements (3) interacting with these extensions (5) can be inserted into the receptacles (1). In the locking position, the locking elements (3) are supported in the receptacles (1) and exert a bearing pressure, directed at least vertically downwards, on the stop-log elements (2). <IMAGE>

IPC 1-7

**E02B 7/22; E02B 7/54**

IPC 8 full level

**E02B 7/22** (2006.01); **E02B 7/54** (2006.01)

CPC (source: EP)

**E02B 7/22** (2013.01); **E02B 7/54** (2013.01)

Cited by

EP1241299A3; EP0924349A3; CN106968224A; WO2015112447A3; US9376778B2; US9670634B2; US10287740B2

Designated contracting state (EPC)

BE DE LU NL

DOCDB simple family (publication)

**EP 0627529 A1 19941207; EP 0627529 B1 19960904**; DE 59400573 D1 19961010

DOCDB simple family (application)

**EP 94108546 A 19940603**; DE 59400573 T 19940603