

Title (en)

Process for the introduction of a sealing medium in a sealing device.

Title (de)

Verfahren zum Einbringen eines Dichtungsmediums in Dichtungseinrichtungen.

Title (fr)

Procédé pour introduire un produit d'étanchéisation dans un joint.

Publication

**EP 0629751 A2 19941221 (DE)**

Application

**EP 94107063 A 19900910**

Priority

- DE 8910744 U 19890908
- EP 90117399 A 19900910

Abstract (en)

[origin: US5249401A] A sealing device for sealing a joint disposed between two concreting sections, having an impermeable profile preferably fabricated from a synthetic material and constructed in a hood form to be open in cross section. The profile is mounted with the free longitudinal edges of its side portions adjacent to a concrete surface, so that a flow channel is formed therein for receiving a sealing medium between the profile and the concrete surface, where the sealing medium can emerge from between the free longitudinal edges of the profile and the concrete surface. A further sealing device is a body fabricated from a foam material or a foam material band, having a rectangular cross section provided with passage pores, the body being mounted to rest on the concrete surface, so that the flow channel for receiving the sealing medium is formed by the body itself, where the sealing medium emerges from the passage pores into the joint area. In a process for introducing the sealing medium into the sealing device, after establishing the second concreting section, a connection is provided between the outside portion of the concrete and the sealing device by preferably drilling a bore, through which the sealing medium is introduced into the interior of the sealing device.

Abstract (de)

Bei einem Verfahren zum Einbringen eines Dichtungsmediums in Dichtungseinrichtungen (138) wird nach dem Erstellen des zweiten Betonierabschnitts (137) eine Verbindung (139), insbesondere durch Bohren, zwischen der Außenseite des Betons und den Dichtungseinrichtungen (138) geschaffen, durch welche das Dichtungsmedium in das Innere der Dichtungseinrichtung (138) eingebracht wird. <IMAGE>

IPC 1-7

**E04B 1/68**

IPC 8 full level

**E02D 29/16** (2006.01); **E04B 1/68** (2006.01); **E04B 1/684** (2006.01)

CPC (source: EP US)

**E02D 29/16** (2013.01 - EP US); **E04B 1/68** (2013.01 - EP US); **E04B 1/6812** (2013.01 - EP US); **E04B 1/6813** (2013.01 - EP US); **E04B 1/6816** (2013.01 - EP US)

Cited by

DE102004020530A1

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)

**EP 0418699 A1 19910327**; **EP 0418699 B1 19950222**; AT E118854 T1 19950315; AT E153411 T1 19970615; DE 59008512 D1 19950330; DE 59010719 D1 19970626; DE 8910744 U1 19910117; DE 9017874 U1 19920910; DK 0418699 T3 19950327; DK 0629750 T3 19970825; EP 0629750 A2 19941221; EP 0629750 A3 19950118; EP 0629750 B1 19970521; EP 0629751 A2 19941221; EP 0629751 A3 19950215; ES 2068958 T3 19950501; ES 2103518 T3 19970916; GR 3023550 T3 19970829; US 5249401 A 19931005; US 5327693 A 19940712; US 5377469 A 19950103

DOCDB simple family (application)

**EP 90117399 A 19900910**; AT 90117399 T 19900910; AT 94107062 T 19900910; DE 59008512 T 19900910; DE 59010719 T 19900910; DE 8910744 U 19890908; DE 9017874 U 19900910; DK 90117399 T 19900910; DK 94107062 T 19900910; EP 94107062 A 19900910; EP 94107063 A 19900910; ES 90117399 T 19900910; ES 94107062 T 19900910; GR 970401201 T 19970523; US 57883090 A 19900905; US 8583793 A 19930706; US 8609393 A 19930706