

Title (en)
OPEN-END SPINNING PROCESS AND DEVICE

Title (de)
VERFAHREN UND VORRICHTUNG ZUM OFFENEND-SPINNEN

Title (fr)
PROCEDE ET DISPOSITIF DE FILAGE OPEN-END

Publication
EP 0630429 B1 19960320 (DE)

Application
EP 93901595 A 19921218

Priority
• CS 386291 A 19911218
• DE 9201065 W 19921218

Abstract (en)
[origin: WO9312279A1] In order to spin a thread (4) by means of an open-end rotor spinning device, the threads are supplied to a thread guiding surface (16) from which the threads are deposited on the sliding wall (7) of a spinning rotor (1) after crossing a gap (17). An air flow (30) is blown into the spinning rotor (1) through a gap (17), then evacuated from the inside of the spinning rotor (1) without going once again through the gap (17). A device (9, 20) is associated to the gap (17) in order to generate the air flow by generating a pressure drop that makes the air flow (30) through the gap (17) into the spinning rotor (1).

IPC 1-7
D01H 4/08

IPC 8 full level
D01H 4/08 (2006.01); **D01H 4/38** (2006.01)

CPC (source: EP US)
D01H 4/08 (2013.01 - EP US)

Designated contracting state (EPC)
DE GB IT

DOCDB simple family (publication)
WO 9312279 A1 19930624; CZ 279489 B6 19950517; CZ 281016 B6 19960515; CZ 286393 A3 19940413; CZ 386291 A3 19941215; DE 59205789 D1 19960425; EP 0630429 A1 19941228; EP 0630429 B1 19960320; JP H07508315 A 19950914; RU 2088706 C1 19970827; SK 386291 A3 19950607; SK 6094 A3 19940907; US 5414990 A 19950516

DOCDB simple family (application)
DE 9201065 W 19921218; CS 286393 A 19921218; CS 386291 A 19911218; DE 59205789 T 19921218; EP 93901595 A 19921218; JP 51052493 A 19921218; RU 93052399 A 19921218; SK 386291 A 19911218; SK 6094 A 19921218; US 9826493 A 19931202