

Title (en)

Printing method with at least one image and press for executing this method.

Title (de)

Druckverfahren mit mindestens einem Bild und einer Presse zur Durchführung dieses Verfahrens.

Title (fr)

Procédé d'impression d'au moins une image et presse pour la mise en oeuvre.

Publication

EP 0631209 A1 19941228 (FR)

Application

EP 94401375 A 19940620

Priority

FR 9307608 A 19930623

Abstract (en)

The invention relates to a method for printing at least one image, with a determined number of copies, using a press, by transfer of a pigment vehicle between an intermediate transfer element obtained by magnetic imaging and a printing medium, comprising at least: a phase of automatic production of the intermediate transfer element in the press by developing, on a substrate, zones each having a different affinity with the pigment vehicle, characterised in that an insulating and hardenable magnetic material is fixed on the substrate in order to constitute these zones having different affinities, the insulating and hardenable magnetic material is cured and subjected to an electrostatic charge by any device capable of charging it at the surface in order to give the regions the affinity with the pigment vehicle; the pigment vehicle having electrostatic properties is deposited on the electrostatically charged parts of cured material and finally the pigment vehicle is transferred onto the printing support by direct contact with the intermediate transfer element. <IMAGE>

IPC 1-7

G03G 15/22; G03G 19/00; B41C 1/10

IPC 8 full level

G03G 15/05 (2006.01); **B41C 1/10** (2006.01); **G03G 15/22** (2006.01); **G03G 19/00** (2006.01)

CPC (source: EP US)

B41C 1/1075 (2013.01 - EP US); **G03G 15/228** (2013.01 - EP US); **G03G 19/00** (2013.01 - EP US); **Y10S 101/37** (2013.01 - EP);
Y10S 101/48 (2013.01 - EP)

Citation (search report)

- [XAY] EP 0097954 A1 19840111 - DU PONT [US]
- [YA] US 4122456 A 19781024 - BERKOWITZ AMI E, et al
- [YA] EP 0029877 A1 19810610 - GEN ELECTRIC [US]
- [A] US 4514744 A 19850430 - SAITO HIROYUKI [JP], et al
- [A] US 5140370 A 19920818 - KASAI TOSHIHIRO [JP], et al
- [DA] US 3804511 A 19740416 - RAIT J, et al
- [DA] US 5129321 A 19920714 - FADNER THOMAS A [US]
- [YA] PATENT ABSTRACTS OF JAPAN vol. 7, no. 262 (P - 238)<1407> 22 November 1983 (1983-11-22)
- [A] PATENT ABSTRACTS OF JAPAN vol. 10, no. 19 (P - 423)<2076> 24 January 1986 (1986-01-24)
- [A] PATENT ABSTRACTS OF JAPAN vol. 6, no. 82 (P - 116)<960> 20 May 1982 (1982-05-20)

Cited by

EP0989469A1; US6320529B1

Designated contracting state (EPC)

BE CH DE ES FR GB IT LI NL

DOCDB simple family (publication)

EP 0631209 A1 19941228; EP 0631209 B1 19971203; CA 2126283 A1 19941224; DE 69407099 D1 19980115; DE 69407099 T2 19980326;
FR 2709572 A1 19950310; FR 2709572 B1 19951027; JP 2763494 B2 19980611; JP H07146604 A 19950606; US 5644987 A 19970708

DOCDB simple family (application)

EP 94401375 A 19940620; CA 2126283 A 19940620; DE 69407099 T 19940620; FR 9307608 A 19930623; JP 14865394 A 19940607;
US 26250094 A 19940620