

Title (en)

Device for retracting a flexible hose.

Title (de)

Vorrichtung zum Zurückziehen eines biegsamen Schlauches.

Title (fr)

Dispositif pour le retrait d'un tuyau flexible.

Publication

EP 0631796 A1 19950104 (EN)

Application

EP 94201796 A 19940622

Priority

NL 9301097 A 19930623

Abstract (en)

An installation for taking up a flexible hose (1) for conveying liquid, such as a fire hose, comprises two pairs of turning pinch elements placed opposite one another (7,8,14,15), the pinch elements of each pair defining a nip of variable nip dimension, through which nips the hose can be transported in order to expel residual liquid therefrom, which variable nip dimension can be enlarged to permit the passage of a coupling (4) present in the hose. The nip dimensions are variable independently of one another and the nips are positioned with respect to one another in such a way that the hose can continuously be held compressed by at least one of the nips. <IMAGE>

IPC 1-7

A62C 33/02

IPC 8 full level

A62C 33/02 (2006.01)

CPC (source: EP)

A62C 33/02 (2013.01)

Citation (search report)

- [XA] US 4452135 A 19840605 - HAYES ROBERT H [US]
- [YA] EP 0360603 A2 19900328 - SHOWA IND CORP [JP]
- [YA] US 3866532 A 19750218 - OGDEN JR GRANT M
- [A] US 1915632 A 19330627 - EARL MARKS

Cited by

CN103998103A; CH701833B1; CN112221064A; CN103706069A; EP2258450A1; CH701223A1; CN107693987A; CN110467043A; CN113942880A; NL2007956C2; JP2015507484A; RU2625428C2; US8376202B2; US9969594B2; US9494256B2; US2014197219A1; CN104689504A; US9399560B2; NL2028656B1; WO2013095116A3; WO2023282745A1; WO2024022331A1

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

EP 0631796 A1 19950104; EP 0631796 B1 19970910; AT E157890 T1 19970915; DE 69405482 D1 19971016; DE 69405482 T2 19980115; DK 0631796 T3 19971013; ES 2109593 T3 19980116; GR 3025243 T3 19980227; NL 9301097 A 19950102

DOCDB simple family (application)

EP 94201796 A 19940622; AT 94201796 T 19940622; DE 69405482 T 19940622; DK 94201796 T 19940622; ES 94201796 T 19940622; GR 970402879 T 19971104; NL 9301097 A 19930623