

Title (en)
PRESS-DEVICE FOR SECURING LACES.

Title (de)
DRUCKKNOPF ZUR ARRETIERUNG VON SCHNÜRSENKELN.

Title (fr)
DISPOSITIF A PRESSION POUR LE BLOCAGE DE LACETS.

Publication
EP 0632699 A1 19950111 (DE)

Application
EP 93906604 A 19930324

Priority
• DE 4209425 A 19920324
• EP 9300715 W 19930324

Abstract (en)
[origin: US5315741A] PCT No. PCT/EP93/00715 Sec. 371 Date Sep. 2, 1993 Sec. 102(e) Date Sep. 2, 1993 PCT Filed Mar. 24, 1993 PCT Pub. No. WO93/18678 PCT Pub. Date Sep. 30, 1993. A snap fastener for securing shoe laces comprises two openings disposed diametrically to each other through which the shoe laces are passed. The openings extend longitudinally through the snap fastener when the latter is opened. An inner sleeve is in a larger outer sleeve such that it is longitudinally movable relative thereto. The inner sleeve accommodates an inner ring. When the pressure is exerted on the outer sleeve, the ring is made to rotate as the longitudinal movement is converted into a horizontal circular movement so that the shoe laces are immovably clamped by the snap fastener.

IPC 1-7
A43C 7/00; **A43C 7/04**; **B65D 63/14**; **B65D 63/16**; **B65D 33/16**

IPC 8 full level
A43C 7/00 (2006.01); **A43C 7/04** (2006.01); **B65D 33/16** (2006.01); **B65D 63/14** (2006.01); **B65D 63/16** (2006.01)

CPC (source: EP US)
A43C 7/00 (2013.01 - EP US); **A43C 11/165** (2013.01 - EP US); **Y10T 24/3703** (2015.01 - EP US); **Y10T 24/3708** (2015.01 - EP US); **Y10T 24/3716** (2015.01 - EP US); **Y10T 24/3984** (2015.01 - EP US)

Designated contracting state (EPC)
AT BE CH DE DK ES FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)
US 5315741 A 19940531; AT E144385 T1 19961115; CA 2120013 A1 19930930; DE 4209425 C1 19930902; DE 59304304 D1 19961128; EP 0632699 A1 19950111; EP 0632699 B1 19961023; WO 9318678 A1 19930930

DOCDB simple family (application)
US 9021593 A 19930902; AT 93906604 T 19930324; CA 2120013 A 19930324; DE 4209425 A 19920324; DE 59304304 T 19930324; EP 9300715 W 19930324; EP 93906604 A 19930324