

Title (en)
SEALING DEVICE FOR THE BOTTOM SIDE OF DOORS

Title (de)
BODENSEITIGE DICHTUNGSVORRICHTUNG FÜR TÜREN

Title (fr)
DISPOSITIF D'ETANCHEITE POUR PARTIE INFERIEURE DE PORTES

Publication
EP 0633975 B1 19970910 (DE)

Application
EP 93903893 A 19930130

Priority
EP 9300217 W 19930130

Abstract (en)
[origin: WO9417276A1] A threshold profiled rod (10) with a cap (12) is fixed to the floor and an in principle T-shaped profiled rod (20) is fixed to the door leaf (1). It comprises a star-shaped tilting element (24) having three legs. This tilting element is linked at its apex to a rib (22) of the profiled rod by a soft strip (29) which serves as a hinge. In addition, the connection between an inner leg (26) of the tilting element and a horizontal rib (23) is provided by means of an elastic band (26a). The figure shows the open position. When the door is closed, a lower leg (25) of the tilting element strikes the inner side of the cap, the tilting element snaps over and an outer leg (27) of the tilting element covers the outer side of the cap, at the same time as a soft sealing strip (28) comes to lie on the outer side of the cap. When the door leaf is opened, the tilting element automatically snaps back into the open position.

IPC 1-7
E06B 7/23; E06B 1/70

IPC 8 full level
E06B 7/20 (2006.01); **E06B 7/23** (2006.01); **E06B 1/70** (2006.01)

CPC (source: EP)
E06B 7/20 (2013.01); **E06B 1/70** (2013.01); **E06B 2001/707** (2013.01)

Designated contracting state (EPC)
BE DE FR IT LU NL

DOCDB simple family (publication)
WO 9417276 A1 19940804; DE 59307344 D1 19971016; EP 0633975 A1 19950118; EP 0633975 B1 19970910

DOCDB simple family (application)
EP 9300217 W 19930130; DE 59307344 T 19930130; EP 93903893 A 19930130