

Title (en)

Method and apparatus for treating a textile sheet-like material.

Title (de)

Verfahren zur Behandlung einer textilen Warenbahn sowie Vorrichtung zur Durchführung desselben.

Title (fr)

Procédé et appareil de traitement d'une matière textile en bande.

Publication

**EP 0640710 A2 19950301 (DE)**

Application

**EP 94112708 A 19940813**

Priority

- DE 4328256 A 19930823
- DE 4329844 A 19930903
- DE 4426336 A 19940725

Abstract (en)

What is described is a method for treating a textile fabric web, in which a predetermined length of the fabric web is arranged within a treatment appliance, an endless fabric-web loop is made from the fabric web and the fabric-web loop is subsequently transported within the treatment appliance. At the same time, during its transport, the fabric-web loop is subjected to a mechanical and/or thermal treatment, such that, in particular, the volume, handle, surface pattern or water content of the fabric-web loop is thereby varied in a controlled manner, a higher or lower pressure than the particular ambient pressure being set in the treatment appliance. An apparatus for carrying out the method has a treatment appliance which is designed as a pressure-tight autoclave closed on all sides. The autoclave is provided with a loading orifice closeable in a gas-tight manner and with an internal transport appliance, the treatment appliance being assigned an overpressure or underpressure source.

Abstract (de)

Es wird ein Verfahren zur Behandlung einer textilen Warenbahn beschrieben, bei dem eine vorgegebene Länge der Warenbahn innerhalb einer Behandlungseinrichtung angeordnet, dort aus der Warenbahn eine endlose Warenbahnschleife hergestellt und anschließend die Warenbahnschleife innerhalb der Behandlungseinrichtung transportiert wird. Hierbei wird die Warenbahnschleife während ihres Transportes einer mechanischen und/oder thermischen Behandlung unterworfen, derart, daß hierdurch insbesondere das Volumen, der Griff, das Oberflächenbild oder der Wassergehalt der Warenbahnschleife gezielt verändert wird, wobei in der Behandlungseinrichtung ein größerer oder kleinerer Druck als der jeweilige Umgebungsdruck eingestellt wird. Eine Vorrichtung zur Durchführung des Verfahrens weist eine Behandlungseinrichtung auf, die als allseitig geschlossener druckdichter Autoklave ausgebildet ist. Der Autoklave ist mit einer gasdicht verschließbaren Beschickungsöffnung und einer innenliegenden Transporteinrichtung versehen, wobei der Behandlungseinrichtung eine Überdruck- oder Unterdruckquelle zugeordnet ist.

IPC 1-7

**D06B 3/28**

IPC 8 full level

**D06B 3/28** (2006.01)

CPC (source: EP KR US)

**D06B 3/26** (2013.01 - KR); **D06B 3/28** (2013.01 - EP US); **D06B 23/205** (2013.01 - EP)

Cited by

WO9950493A1; RU2707795C2; DE10124542B4; EP0945538A1; DE19813593C2; DE10349384B4; EP1526204A3; US10895031B2; WO2016180389A1; WO2016180390A1

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

**EP 0640710 A2 19950301**; **EP 0640710 A3 19970312**; DE 4426336 A1 19950302; KR 100186840 B1 19990501; KR 950006072 A 19950320; US 5524359 A 19960611

DOCDB simple family (application)

**EP 94112708 A 19940813**; DE 4426336 A 19940725; KR 19940020745 A 19940823; US 31743994 A 19940810