

Title (en)

A METHOD FOR CASCADING OF MICROBASES.

Title (de)

VERFAHREN ZUR KASKADIERUNG VON MIKROBASISSTATIONEN.

Title (fr)

MONTAGE EN CASCADE DE MICROBASES.

Publication

EP 0641504 A1 19950308 (EN)

Application

EP 94911336 A 19940315

Priority

- SE 9400224 W 19940315
- US 3561793 A 19930323

Abstract (en)

[origin: WO9422245A1] In a radiotelephone communication system of the type having a plurality of cascaded connected base stations or microbases, a PCM link transmits a TDM signal having a plurality of frames that are divided into time slots that correspond to control time slots and voice channels. At a source base station, the frame synchronization position of the TDM signal is preferably moved to a time slot that is in the intended control time slot for a destination base station. The TDM signal is then transmitted to the destination base station, and the received TDM signal at the destination base station includes a new frame structure having consecutively renumbered time slots. The method of the present invention allows standardized equipment to be used at both the source and destination base stations.

IPC 1-7

H04J 3/08; **H04Q 11/04**

IPC 8 full level

H04J 3/06 (2006.01); **H04Q 7/30** (2006.01); **H04W 88/08** (2009.01); **H04Q 7/36** (2006.01)

CPC (source: EP)

H04J 3/0602 (2013.01); **H04W 88/08** (2013.01)

Citation (search report)

See references of WO 9422245A1

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB GR IE IT LI LU NL PT SE

DOCDB simple family (publication)

WO 9422245 A1 19940929; AU 6388094 A 19941011; EP 0641504 A1 19950308; TW 232106 B 19941011

DOCDB simple family (application)

SE 9400224 W 19940315; AU 6388094 A 19940315; EP 94911336 A 19940315; TW 83102476 A 19940322