

Title (en)

Winding-type high-voltage resistant, resistive cord for preventing noises.

Title (de)

Geräuschunterdrückender hochspannungsfester Kabel mit gewundener Widerstand.

Title (fr)

Câble haute tension à résistance enroulée et à suppression des bruits.

Publication

**EP 0644556 A2 19950322 (EN)**

Application

**EP 94105235 A 19940405**

Priority

JP 10516693 A 19930406

Abstract (en)

There is disclosed a winding-type high-voltage resistant, resistive cord for preventing noises which comprises a fiber bundle (11), a core (12), a metal small-gage wire (13), a removal layer (15), an internal layer (16), an insulating layer (17), a braid (18), and a sheath (19), wherein the core (12) is formed by immersing the fiber bundle (11) in a fluorocarbon rubber coating containing fluorocarbon rubber filled with carbon and ferrite and regulated by a solvent which is MEK to impregnate the fiber bundle (11) therewith, and the internal layer (16) is made mainly of polyethylene (PE) similar to the insulating layer (17). The core (12) is not removed from the fiber bundle (11) during extrusion of the internal layer (16) which has good adhesion to the insulating layer (17), which prevents lowering of resistance to voltage due to corona discharge. The winding-type high-voltage resistant, resistive cord ensures sufficient resistance to voltage if a high voltage is required. <IMAGE>

IPC 1-7

**H01B 7/00**

IPC 8 full level

**H01B 7/00** (2006.01); **H01B 13/00** (2006.01)

CPC (source: EP)

**H01B 7/0063** (2013.01)

Cited by

EP1995850A1; US6054028A; US6252172B1; EP0655750A3; CN109712749A; US2013133921A1; CN104067355A; CN104700960A

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

**EP 0644556 A2 19950322**; **EP 0644556 A3 19950621**; **EP 0644556 B1 19970806**; DE 69404791 D1 19971030; DE 69404791 T2 19980205; JP H06295622 A 19941021

DOCDB simple family (application)

**EP 94105235 A 19940405**; DE 69404791 T 19940405; JP 10516693 A 19930406