

Title (en)

Device for driving or putting under tension of a supple protection element such as a web, a curtain, or an apron

Title (de)

Getrieb- und Unterspannungsetzungsvorrichtung eines biegsamen Schutzelements wie eines Bandes, eines Vorhangs oder einer Schürze

Title (fr)

Dispositif d'entraînement et de mise sous tension d'un élément souple de protection, tel qu'une bande, un rideau ou un tablier

Publication

EP 0645518 B1 19970108 (FR)

Application

EP 94440061 A 19940923

Priority

FR 9311767 A 19930929

Abstract (en)

[origin: EP0645518A1] The invention relates to a device for operating and tensioning a flexible protective element (2), such as a band (3), a curtain or a shutter, comprising a winding control shaft (5) and an unwinding control shaft (6) which are driven by means of a motor (12, 13) fitted with a brake (14, 15) which is activated so as to stop braking when one of these motors (12, 13) is switched on. With a view to ensuring that this flexible protective element is kept taut between the winding control shaft (5) and the unwinding control shaft (6), this operating and tensioning device comprises means (16) for controlling the power supplied to the motors (12, 13) so that a torque is generated by one of these motors (12, 13), which torque resists the operation of the other motor (13, 12) respectively, during the stage in which the flexible protective element (2) is being unwound or wound up, respectively. <IMAGE>

IPC 1-7

E06B 9/70

IPC 8 full level

E06B 9/70 (2006.01)

CPC (source: EP US)

E06B 9/70 (2013.01 - EP US)

Cited by

FR3127010A1; FR3127011A1; WO2008102141A1; EP4148227A1; EP2573294A1; AU2008217599B2; EP2487319A1; US8281795B2

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

EP 0645518 A1 19950329; EP 0645518 B1 19970108; AT E147475 T1 19970115; DE 69401410 D1 19970220; DE 69401410 T2 19970619; ES 2098113 T3 19970416; FR 2710685 A1 19950407; FR 2710685 B1 19951222; US 5547009 A 19960820

DOCDB simple family (application)

EP 94440061 A 19940923; AT 94440061 T 19940923; DE 69401410 T 19940923; ES 94440061 T 19940923; FR 9311767 A 19930929; US 31105994 A 19940923