

Title (en)
Detachable sabot for a subcalibre projectile

Title (de)
Abwerfbarer Treibspiegel für ein Unterkalibergeschoss

Title (fr)
Sabot détachable pour projectile sous-calibré

Publication
EP 0645600 B1 19961009 (DE)

Application
EP 94112866 A 19940818

Priority
CH 289193 A 19930924

Abstract (en)
[origin: US5404816A] A releasable sabot for a subcaliber projectile. A relatively large danger zone exists for troops in which they can be injured by sabot splinters during the firing of subcaliber projectiles, with the releasable sabots, from a helically grooved weapon barrel, and in order to minimize this danger zone, the sabot of this invention is of a one piece plastic material construction and includes longitudinal slots and cooperative fracture point locations, wherein the longitudinal slots extend continuously from the sabot front end to the gastight region of the driving band, with the longitudinal slots, in cross section, having enlargements in the slot base regions.

IPC 1-7
F42B 14/06

IPC 8 full level
F42B 14/06 (2006.01)

CPC (source: EP US)
F42B 14/064 (2013.01 - EP US)

Cited by
AU2018200773B2; EP0989381A2; US8561544B2; WO2009021607A1; WO2017001428A1; WO2012034631A1; DE102010045474A1; US9528806B2; US8250988B2; US10996035B2

Designated contracting state (EPC)
BE CH DE ES FR GB IT LI NL SE

DOCDB simple family (publication)
EP 0645600 A1 19950329; EP 0645600 B1 19961009; CA 2130840 A1 19950325; CA 2130840 C 19980217; DE 59400818 D1 19961114; EG 21731 A 20020227; ES 2094604 T3 19970116; FI 108964 B 20020430; FI 944415 A0 19940923; FI 944415 A 19950325; JP 3388640 B2 20030324; JP H07159098 A 19950620; NO 300824 B1 19970728; NO 942894 D0 19940804; NO 942894 L 19950327; US 5404816 A 19950411

DOCDB simple family (application)
EP 94112866 A 19940818; CA 2130840 A 19940825; DE 59400818 T 19940818; EG 45694 A 19940731; ES 94112866 T 19940818; FI 944415 A 19940923; JP 21498394 A 19940908; NO 942894 A 19940804; US 28619694 A 19940808